DRILLERS LOG

API NO: 15 - 125 - 32158 - 00 - 00

S. 33 T. 33 R. 14 E. W.

OPERATOR: PITMAN, JOHN DOUGLAS REVOCABLE TRUST

LOCATION: NW SE NW NE

COUNTY: MONTGOMERY

ADDRESS: 222 E. SHERIDAN #7, OKLAHOMA CITY, OK 73104

ELEV. GR.: 890

DF: KB:

WELL #: B - 2 LEASE NAME: A.D. BERRY

FOOTAGE LOCATION: 4450 FEET FROM (N) (S) LINE 1975 FEET FROM (E) (W) LIN

CONTRACTOR: FINNEY DRILLING COMPANY

GEOLOGIST: GARY SHEARHART

SPUD DATE: 3/2/2012

TOTAL DEPTH: 808 P.B.T.D.

DATE COMPLETED: 3/5/2012

OIL PURCHASER: C.V.R. ENERGY

CASING RECORD

REPORT OF ALL STRINGS - SURFACE, INTERMEDIATE, PRODUCTION, ETC.

PURPOSE OF STRING	SIZE HOLE DRILLED	SIZE CASING SET (in O.D.)	WEIGHT LBS/FT	SETTING DEPTH	TYPE CEMENT	SACKS	TYPE AND % ADDITIVES
SURFACE:	12 ¼	8 5/8	28	21.60	I	10	SERVICE COMPANY
PRODUCTION:	6 3/4	4.5	9.5	801	50-50	115	SERVICE COMPANY

WELL LOG

CORES: #1 - 739 - 759

RAN:

RECOVERED: 20 FT

ACTUAL CORING TIME:

FORMATION	TOP	BOTTOM
TOP SOIL	0	8
CLAY	8	20
SHALE	20	47
LIME	47	52
SAND & SHALE	52	116
LIME	116	117
SAND & SHALE	117	132
LIME	132	134
SHALE	134	261
LIME	261	269
SHALE	269	283
SAND	283	356
SHALE	356	378
SAND	378	417
SAND & SHALE	417	436
SAND	436	445
SAND & SHALE	445	529
LIME	529	539
SHALE	539	548
SAND	548	567
SHALE	567	720
LIME	720	732
SHALE	732	735
LIME	735	737
OIL SAND	737	779
SHALE	779	794
LIME	794	808 T.D.

FORMATION	TOP	BOTTOM