

WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas


31-33-6E

Company- CREST PETROLEUM, INC. & DUKE & WOOD
Farm- Berry "C" No. 5

SEC. 31 T. 33 R. 6E
NE SE SE

Total Depth. 2220
Comm. 8-13-54 Comp. 8-28-54
Shot or Treated.
Contractor. Fortier & Wright Drlg. Co.
Issued. 10-2-54

County Cowley
KANSAS



Elevation. 1168

Production. IPP 50 BOPD / tr. wtr

CASING:

8 5/8" 68' cem. w/50 sx
5 1/2" 2215' cem. w/60 sx

Figures Indicate Bottom of Formations.

lime	35
shale	60
lime hard	67
lime & shale	84
lime hard	99
lime & shale, redbed	215
lime	285
lime & shale	1400
shale	1760
sand	1816
shale	1895
shale & lime	1950
shale, sdy shale	2070
shale	2143
sand	2146
Cored: sand	2146 to 2196
(Full recovery, 21 feet of oil saturation)	
Top of plug	2196
sand	2220
Total depth	

Tops:
Layton sdy Zone 2136
Layton sand 2153

Perforated:
35 shots from 2163-2168 (Lane Wells Measurement
2157-2162
Swabbed 3 1/2 bbls. oil per hr - little wtr-
putting well on pump.