

30-33-6E


THE TEXAS COMPANY
James Lorton No. 1

SEC. 30 T. 33 R. 6 E
NEc SW

Total Depth. 3520
Comm. 10-11-41 Comp. 3-31-42
Shot or Treated.
Contractor.
Issued. 4-18-42

County Cowley.

Rotary 3520



CASING.

10 3/4" 75'

Elevation. 1257 L 1/5

Production. DRY.

Figures Indicate Bottom of Formations.

lime hard rock	70	shale	3320
lime & flint rock	110	broken chert	3328
shale	115	shale & chert	3348
lime	225	lime shale & chert	3369
shale	285	lime	3470
lime	420	shale and lime	3501
lime and shale	530	Arbuckle lime	3509
shale	545	lime & chert	3520
broken lime and shale	610	Total Depth.	
shale and shells	680		
lime	690	TOPS.	
shale	780	Lansing	1780
broken lime	910	Sand	2962
shale	940	Mississippi	3035
shale lime shells	1020		
shale	1060		
broken lime and shale	1165		
shale and shells	1290		
sand white	1320		
shale & shells	1370		
sand white	1395		
shale and shells	1470		
lime and shale	1565		
shale lime shells	1710		
shale and shells	1770		
lime	1790		
lime and shale	1835		
shale	1850		
sand	1910		
shale	1930		
shale and lime	2130		
shale	2235		
sdv shale	2260		
sand	2275		
sdv shale	2315		
shale	2400		
shale and sand	2415		
sdv shale	2550		
lime and shale	2610		
shale	2690		
lime and shale	2735		
shale	2745		
shale and lime	2800		
shale	3035		
lime and chert	3041		
lime and chert	3211		
lime & chert shale	3220		
shale and lime	3245		

Stalnak 1805-1835

Cored from 2964-74