State Geological Survey
WICHITA, BRANCH

Dilts

DRILLERS LOG

S. 17 T. 34 R. 12E E/W

API No. 15 – 019 (County) – 20,719 (Number)

Loc. ~~700' FWL & 180' FSL~~

County Chautauqua

640 Acres



Locate well correctly

Elev.: Gr. _____

DF _____ KB _____

Operator: Harold Holroyd

Address: Rt. #1, Sedan, Ks. 67361

Well No.: 1

Lease Name: Holroyd

Footage Location: feet from (N) (S) line; feet from (E) (W) line

Principal Contractor: Dobbie Drilling Co.

Geologist:

Spud Date: 12/3/76

Total Depth: 965

P.B.T.D.:

Date Completed: 12/4/76

Oil Purchaser:

CASING RECORD

Report of all strings set—surface, intermediate, production, etc.

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
SURFACE	9"	7"	17	50	portland	15	3% cal.
PRODUCTION	6¼"	4½"					

WELL LOG

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Formation	Top	Btm.
soil	0	12
shale	12	17
lime	17	40
sand	40	90
shale	90	289
sand	289	344
shale	344	378
sand	378	385
shale	385	390
lime	390	397
sandy shale	397	405
lime	405	414
shale	414	580
lime	580	585
sandy shale	585	727
lime	727	734
sandy shale	734	915
lime	915	917
shale	917	928
lime	928	930
shlae	930	935
lime (cap)	935	944
shale	944	947
sand - odor	947	948
Core #1	948	965

RECEIVED
STATE CORPORATION COMMISSION
JAN 17 1977
CONSERVATION DIVISION
Wichita, Kansas