

BARTLETT PROSPECT Core Hole #2

CRA, Inc.

DRILLING, COMPLETION AND WORKOVER RECORD

ELEVATION-		ELEV-		OPERATOR-		CRA, Inc.	
FORMATION	DEPTH	SUB-SEA	THICK	SOURCE	FARM-	Pickering	NO 1
Squirrel Ss.	134'		10	IE Log	LOCATION-	NW SE SE	
B'ville Ss.	234'		18	"	POSTAGE S. T. R. (SUR.)	28-345-202	
Mississippian Ls.	580'		N.R.	"	CO. PA.	Labette	
T. D.	601'			"	STATE	Kansas	
					AREA	Bartlett Field	
					COMMENCED DRILLING-	9-18-65	
					COMPLETED DRILLING-	9-20-65	
					FIRST PRODUCTION-	Plugged	
					FLOW/GAS LIFT/PUMP-		

INITIAL PRODUCTION DATA										
PRODUCING ZONE	OIL GRAVITY °API	PRODUCTION			SIZE CHOKES	WV	VSP	PRESSURE, PSI		
		OIL, BOPD	WATER, BWPD	SAL, MCFG				CP	CSF	ISWF

CASING RECORD (PRESENT HOLE)												
SIZE A.P.I.	WT	THD.	GRADE	BS	T&C	SMLS OR OTHER	SHOE DEPTH	NEW OR MATH. CLASS	DRILLED HOLE	CEMENT SACCS TYPE		DEPTH IF PERFD
8-5/8"							26			None.		
									</			

PERFORATIONS						
CASING SIZE	FROM	TO	SIZE OF PERFORATIONS	NUMBER OF HOLES	DISTANCE BETWEEN CENTERS	METHOD OF PERF'ING

9-16-65 Spudded well.
9-17-65 Drlg. @ 20'. Set 29' of 7" surf. w/ 20 sq. int. Drld 140'. Core bbl wouldn't

go due to crooked hole. Skidded rig 5'.

9-18-65

Spudded new hole. Set 26' of 8-5/8" surf. cas. no cut. Drl'd to 602'. No shows reported. Top of Miss. Lm. 580'. Show in top of line. (Cored from 131'-141.5' rec. 2' laminated sd and sh. bleeding w/rt rest sty sh. Squirre' Sa. Cored from 582'-602' in Miss. Lm. Rec. 6" sty lm. bleeding oil; " cong. sd, sh and lm; 15 1/2' lm.

Plugging well 9-20-65. 7 sk cut on bottom. Mud to 150' bridge @ 150' w/ 8 sk cut. Mud to 65'. Bridge @ 65'. 1 sk cut @ 65'. Dirt to top and 2 sk cut.

Form No. 1000

To: CRA Prod., KC

Assoc. Oil & Gas

C. C. Murphy

Well File