


SINCLAIR PRAIRIE OIL CO.
E.W.Shurtz No. 2.

SEC.29 T.34 R. 3 E
NE NW NE

Total Dophth. 3395'
Comm. 10-1-41 Comp. 10-28-41
Shot or Treated. 60 Qts.10-24-41 3370-94
Contractor. Harbar Drlg.Co.
Issued. 12-27-41

County. Cowley

Rotary O-3352
Standard 3352-95



CASING:

10 $\frac{3}{4}$ " 110' LI
7" 3351' LI
5 $\frac{1}{2}$ " 62' of liner set on btm of
hole, perforated up to 25'

Elevation.

Production. Pot.297 B.

Figures Indicate Bottom of Formations.

surface clay	10	shale	3325
shale	45	shale varicolored	3329
shale-shells	80	shale green	3332
lime	123	red rock	3335
lime & shale	160	shale green	3343
red rock	170	shale greenish-gy	3352
lime, shale, red rock	280	sdv shale	3363
shale & shells	315	sand	3387
sand	350	shale	3388
sdv shale & shells	455	sand, trace of chat	3395
lime shells	490	Total Depth.	
shale & lime shells	595		
red rock & shells	675		
shale & shells	735		
sand, shale, shells	805		
shale & lime	975		
shale & shells	1045		
lime	1110		
shale & shells	1250		
sdv shale	1285		
shale	1340	Bartlesville 3363-95	
shale & sand	1350		
shale & lime	1400		
lime	1445		
shale	1480		
lime	1500		
shale & shells	1555		
lime	1585		
shale & shells	1600		
shale	1630		
lime	1690		
shale	1715		
lime	1840		
lime & shale	1905		
shale	1965		
lime	2000		
shale	2015		
sand & shale	2085		
shale	2215		
lime	2225		
sand	2325		
sand & lime	2350		
shale & shells	2380		
lime	2385		
shale & brkn lime	2425		
shale	2660		
sdv lime	2780		
sand	2805		
shale	2910		
lime	2980		
sand	3000		
lime	3045		
lime brkn	3050		
shale	3065		
lime	3170		
shale	3260		
sdv lime	3270		