

State Geological Survey WICHITA BRANCH

DRILLERS LOG


API No. 15 - 125 - 21,071
County Number

S. 9 T. 35 R. 14E_W

Loc. 500SNL 1500WEL

County Montgomery

640 Acres



Locate well correctly

Elev.: Gr. _____

DE KB

Operator PAUL A. LAMB	
Address Box 273, Coffeyville, Ks. 67337	
Well No. 5	Lease Name Blundell
Footage Location feet from (N) (S) line feet from (E) (W) line	
Principal Contractor Dobbie Drilling Co.	Geologist
Spud Date 9/30/76	Total Depth 1356 P.B.T.D.
Date Completed 10/7/76	Oil Purchaser

CASING RECORD

Report of all strings set—surface, intermediate, production, etc.

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs./ft.	Setting depth	Type cement	Sacks	Type and percent additives
SURFACE	9"	7"		129		40	3% cal.
PRODUCTION	6 1/4"	none					

WELL LOG

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Formation	Top	Btm.	Formation	Top	Btm.	Formation	Top	Btm.
soil	0	8	shale	1035	1043			
clay	8	15	lime	1043	1064			
shale	15	60	shale	1064	1069			
sandy shale	60	68	lime	1069	1085			
shale lime	68	70	shale	1085	1104			
sandy shale	70	85	shale	1104	1106			
shale	85	179	shale	1106	1113			
lime	179	182	lime	1113	1115			
sand	182	184	shale	1115	1129			
sandy shale	184	502	lime	1129	1131			
lime	502	508	shale	1131	1178			
sandy shale	508	650	sand	1178	1184			
lime	650	654	shale	1184	1229			
sandy shale	654	656	B'ville sand	1229	1236			
lime	656	667	Core #2	1236	1256			
sandy shale	667	679	shale	1256	1327			
lime	679	689	blue sand	1327	1346			
sandy shale	689	733	shale	1346	1356			
lime	733	771						
Core #1	771	791						
sandy shale	791	877						
lime	877	903						
sandy shale	903	1012						
oswego lime	1012	1035						