

Company - B. B. BLAIR
Farm - Cox No. 1.

SEC. 10-4-10 T. 4 R. 7 E

CSW SW

SW SW

Total Depth. 2175'

Comm. 11-1-43


Shot or Treated.

Contractor.

Issued. 1-29-44

Comp. 1-2-44

County. Marshall
KANSAS



CASING:

12 1/2" 30' 7" 2075'
10" 866'
8 1/4" 1260' UR 1475'

Elevation. 1295

Production. Dry

Figures Indicate Bottom of Formations.

& gravel

0-28	lime sdy	777	lime brown	1760
30	shale gy	809	lime & shale, grey	
33	lime	835	green	1765
48	shale	850	shale sdy- gy &	
56	lime	870	green	1800
59	shale	875	shale	1804
84	lime	881	lime & flint	1836
94	shale	886	lime brown	1870
100	lime	895	lime & flint	1903
105	shale	920	lime gy	1993
113	lime	932	shale green	1998
117	shale	935	lime gy	2037
125	lime - wtr	1000	shale green	2062
130	red	1002	lime	2065
142	lime	1010	shale green	2074
150	shale green & red	1016	2074 equals 2087	
158	lime	1027	lime	2087- 2117
170	shale blue & red	1030	sand wh-fresh wtr	2138
190	lime	1045	sand hd	2147
200	shale	1050	shale sdy brown	2162
220	lime	1075	sand glassy hd	2166
235	shale blue	1082	sand glassy med hd	2175
240	lime	1096	Total Depth.	
246	shale gy	1101		
251	shale dk	1106		
254	lime HFW	1140		
305	shale	1143		
320	lime	1214		
328	shale dk	1219		
331	lime	1231		
350	shale gy	1240		
352	lime	1249		
355	shale red&green-cave	1253		
358	lime	1276		
390	shale gy & red	1282		
393	lime	1287		
403	shale gy	1290		
435	lime	1300		
440	shale	1304		
460	lime	1310		
465	shale blue & green	1315		
475	lime	1331		
478	shale gy	1335		
518	shale green, yellow, red	1350		
525	red	1356		
533	shale blue	1364		
570	lime	1369		
580	shale red	1400		
585	lime	1408		
600	shale red	1418		
607	chert, boulders &			
613	shale red	1429		
617	lime, chert, shale red	1445		
625	lime	1475		
630	lime hd gy	1610		
675	lime wh	1690		
680	lime gy	1696		
685	lime gy & pink	1705		
695	lime brown	1728		
770	lime & shale gy	1740		

Pa Cong?

H?