



(Rules 82-3-130 and 82-3-107)

This form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ninety (90) days after the completion of a well, regardless of how the well was completed.

FOR INFORMATION REGARDING THE NUMBER OF COPIES TO BE FILED AND APPLICATIONS REQUIRING COPIES OF ACO-1 FORMS SEE PAGE TWO (2), SIDE TWO (2) OF THIS FORM.

F Letter requesting confidentiality attached.

C Attach ONE COPY of EACH wireline log run (i.e. electrical log, sonic log, gamma ray neutron log etc.)***Check here if NO logs were run

PLEASE FILL IN ALL INFORMATION. IF NOT AVAILABLE, INDICATE. IF INFORMATION LATER BECOMES AVAILABLE, SUBMIT BY LETTER.

LICENSE # 5537 EXPIRATION DATE 6-30-84

OPERATOR Kenny Brown Enterprises API NO. 15-163-22,1480

ADDRESS P. O. Drawer 340 COUNTY Rooks

Plainville, KS 67663 FIELD

** CONTACT PERSON Kenneth O Brown PROD. FORMATION PHONE 913-434-7236 Indicate if new pay.

PURCHASER LEASE Mowry

ADDRESS WELL NO. 2

WELL LOCATION NW SW NW/4

DRILLING Dreiling Oil, Inc. 990 Ft. from South Line and

CONTRACTOR ADDRESS Box 1000 330 Ft. from West Line of

Victoria, KS 67671 the NW (Qtr.) SEC 28 TWP 10 RGE 18 (W).

PLUGGING Dreiling Oil, Inc. WELL PLAT (Office Use Only)

CONTRACTOR ADDRESS Box 1000 KCC

Victoria, Kansas 67671 KGS

TOTAL DEPTH 3685' PBTB 1435' SWD/REP

SPUD DATE 10-7-83 DATE COMPLETED 10-12-83 PLG.

ELEV: GR 2065 DF 2067 KB 2070 NGPA

DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE application for disposal will follow

Amount of surface pipe set and cemented 174' DV Tool Used?

TYPE OF COMPLETION THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Shut-in Gas, Gas, Dry, Disposal, Injection, Temporarily Abandoned. If OWWO, indicate type of re-completion. Other completion. NGPA filing

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.

A F F I D A V I T

I Kenneth O Brown, being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit. The statements and allegations contained therein are true and correct.

State Geological Survey

ACO-1 Well History CP

Side TWO

WICHITA BRANCH

OPERATOR Kenny Brown Enterprises LEASE NAME Mowry

SEC 28 TWP 10 RGE 18 (33)

WELL NO 2 (W)

FILL IN WELL INFORMATION AS REQUIRED;

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Show Geological markers, logs run, or other Descriptive information.

Formation description, contents, etc.	Top	Bottom	Name	Depth
---------------------------------------	-----	--------	------	-------

<p>X <input type="checkbox"/> Check if no Drill Stem Tests Run.</p> <p><input type="checkbox"/> Check if samples sent Geological Survey.</p> <p>Shale 0'</p> <p>Shale 176'</p> <p>Sand 700'</p> <p>Sand 861'</p> <p>Shale 872'</p> <p>Sand 923'</p> <p>Shale 1105'</p> <p>Anhy. 1421'</p> <p>Shale 1457'</p> <p>Shale 1706'</p> <p>Shale & Lime 2128'</p> <p>Lime & Shale 2380'</p> <p>Lime & Shale 2685'</p> <p>Shale & Lime 2944'</p> <p>Lime 3078'</p> <p>Lime 3207'</p> <p>Lime 3313'</p> <p>Lime 3409'</p> <p>Lime 3503'</p> <p>Lime 3615'</p> <p>T.D. 3685'</p> <p>1st. plug set @ 3645'-25 sacks cement</p> <p>2nd plug set @ 1435'-325 sacks with 5 1/2" casing set. Circulated good.</p> <p>If additional space is needed use Page 2</p>				
---	--	--	--	--

Report of all strings set — surface, intermediate, production, etc.							
				CASING RECORD (New) or (Used)			
Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs./ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 1/4"	8 5/8"		174'	common	130	
		5 1/2"		1435'	Halliburton Light	325	

LINER RECORD			PERFORATION RECORD		
Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval

TUBING RECORD		
Size	Setting depth	Pecker set at