


WELL RECORD

21-10-20W

(Mail to Kansas Geological Survey, 4150 Monroe Street, Wichita, Kansas 67209)



Lease Name: Thomas Well No. 1
 Well Located: SE NW SW, Rooks County, Ks.
SEC 21 TWP 10S RGE 20W
 Operator: BEACON RESOURCES CORPORATION
 Address: 1000 Century Plaza Wichita, Ks. 67202
 Elevation: Ground 2211 D.F. 2263 K.B. 2216 rb
 Type Well: (Oil, gas, dry hole) D&A

Drilling Commenced: 12/23/71 19 Drilling Completed: 12/30/71 19
 Well Completed: 19 Total Depth 3475'
 Initial Production: D&A

Casing Record

Size: 8-5/8" Set at 243' Size: _____ Set at _____
 Size: _____ Set at _____ Size: _____ Set at _____

Liner Record

Size: None set Set from _____ To _____

Cementing

Casing Size	Sacks	Type Cement and Additives
<u>8-5/8"</u>	<u>175</u>	<u>SS Common</u>
_____	_____	_____
_____	_____	_____

Perforations

Formation	Perforated Interval and Number Shots
_____	_____
_____	_____
_____	_____
_____	_____

Electric Log Run (Show type log and depths covered)

None run Sample tops: Anhy. - 1696 (+520); Topeka - 3267 (-1051);
Heebner - 3470 (-1254); T.D. - 3475 (-1259)

21-10-20W

(Fill in formation and related information on reverse side)

cont.
21-10-20d

FORMATION, TESTING AND COMPLETION RECORD

Show Drill Stem Tests,
Well Stimulation and
Production Tests

Formation Top Bottom



Figures Indicate Bottom of Formations

0'	40'	Clay and Surface Soil
40'	247'	Shale
247'	685'	Shale
685'	1190'	Shale with sand Streaks
1190'	1430'	Sand
1403'	1470'	Shale
1470'	1695'	Red Bed And Shale
1696'	1743'	Anhydrite
1743'	1860'	Shale & Shells
1860'	2045'	Shale & Shells
2045'	2365'	Lime & Shale
2365'	2595'	Lime & Shale
2595'	2700'	Lime
2700'	2970'	Lime & Shale
2970'	3120'	Lime & Shale
3120'	3265'	Lime
3265'	3375'	Lime
3375'	3460'	Lime
3460'	3475'	Lime & Shale
3475'	T.D.	

SMP TOPS	DEPTH
ANHY	1696
HEEB	3470
RTD	3475

8EEET