

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company. HEATHMAN-SEELIGSON DRILLING CO.
Farm. Thomas No.2

SEC. 29 10 R. 20W
C SE $\frac{1}{4}$

Total Depth. 3785

Comm. 5-7-55

Comp. 5-17-55


Shot or Treated.

Contractor. Heathman-Seeligson Drilling Co.

Issued. 9-3-55

County Rocks

KANSAS



CASING:
8 5/8 @ 159.58' w/ 125 sx cmt.
5 1/2 @ 3778' w/ 155 sx cmt.

Elevation. 2196 DF

Production. 149 BOPD

Figures Indicate Bottom of Formations.

| | |
|----------------------|------|
| shale & clay | 40 |
| sand, shale & shells | 160 |
| shale & shells | 285 |
| shale & sand | 860 |
| sand | 915 |
| shale, sand & shells | 1170 |
| sand | 1385 |
| red bed & shale | 1665 |
| anhydrite | 1700 |
| shale & shells | 2100 |
| salt & shale | 2270 |
| lime & shale | 2415 |
| shale & shells | 2560 |
| lime & shale | 3400 |
| lime | 3405 |
| lime & shale | 3475 |
| lime | 3730 |
| lime & shale | 3785 |
| Total Depth | |

TOPS: (KB)

| | |
|------------|------|
| Anhydrite | 1665 |
| Heebner | 3443 |
| Toronto | 3463 |
| Lansing-KC | 3481 |
| Arbuckle | 3777 |