

KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
 KANSAS GEOLOGICAL SOCIETY BUILDING
 508 EAST MURDOCK - WICHITA, KANSAS

COMPANY DON E PRATT

SEC. 18 T. 10 R. 24W

FARM A. Hobbs

NO. 1

LOC. SE SE SE

TOTAL DEPTH 3983'

COUNTY Graham

COMM. 3-20-67

COMP. 3-26-67

SHOT OR TREATED

CONTRACTOR L. J. Dreiling

ISSUED 7-15-67

KANSAS

CASING

20	10	
15	8 5/8" 179'	cem w/ 150 sx
12	6	
13	5	

ELEVATION 2428' KB

PRODUCTION 90 BOPD/ NW
 IKC 3872-74, Grav 35.9

FIGURES INDICATE BOTTOM OF FORMATIONS

0'	40'	Surf Soil & Clay	
40'	179'	Shale	
179'	190'	Shale	
190'	1050'	Shale & Shells	
1050'	1130'	Sand	
1130'	1360'	Shale & Shells	
1360'	1498'	Shale & Redbed	
1498'	1500'	Hard Sand	
1500'	1580'	Shale & Redbed	
1580'	1822'	Sand	
1822'	2054'	Shale & Redbed	
2054'	2092'	Anhy.	
2092'	2160'	Shale & Shells	
2160'	2575'	Shale & Shells	
2575'	2795'	Shale & Lime	
2795'	3112'	Shale & Lime	
3112'	3264'	Lime & Shale	
3264'	3540'	Lime & Shale	
3540'	3603'	Lime	
3603'	3748'	Lime	TOPS: SCOUT
3748'	3790'	Lime	Heebner 3700
3790'	3825'	Lime	Toronto 3723
3825'	3840'	Lime	Lansing 3737
3840'	3905'	Lime	B/ Kansas City 3969
3905'	3950'	Lime	
3950'	3983'	Lime	
3983'	T.D.		

STATE OF KANSAS)
)ss
 COUNTY OF ELLIS)

I, Leo F. Dreiling, of the L. J. Dreiling & Sons, Inc., upon oath states that the above and foregoing is a true and correct copy from the Daily Drilling Report from your A. Hobbs #1.

Leo F. Dreiling
 DREILING