

**KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
KANSAS GEOLOGICAL SOCIETY BUILDING
508 EAST MURDOCK - WICHITA, KANSAS**

COMPANY **DON E PRATT OIL OPERATIONS**

SEC. 29 T. 10 R. 24W

FARM **C. Hanna** NO. **1**

LOC. **NE NW NE**

TOTAL DEPTH **3930'**

COUNTY **Graham**


COMM. **8-21-68**

COMP. **9-11-68**

SHOT OR TREATED

CONTRACTOR **L. J. Dreiling & Sons**

ISSUED **10-19-68**



CASING

| | | |
|----|----|-------------------------|
| 20 | 10 | |
| 15 | 8 | 5/8" 153' cem w/ 135 sx |
| 12 | 6 | |
| 13 | 5 | |

ELEVATION **2409' KB**

PRODUCTION **DRY/LANS**

FIGURES INDICATE BOTTOM OF FORMATIONS

| | | |
|-------|-------|----------------------------|
| 0' | 40' | Surface Soil & Sand & Rock |
| 40' | 120' | Yellow Clay & Rock |
| 120' | 153' | Blue Shale |
| 153' | 935' | Shale & Shells |
| 935' | 1025' | Sand |
| 1025' | 1110' | Shale & Sand Streaks |
| 1110' | 1570' | Sand & Shale |
| 1570' | 1758' | Sand |
| 1758' | 2021' | Shale & Redbed |
| 2021' | 2058' | Anhy. |
| 2058' | 2280' | Shale |
| 2280' | 2546' | Shale & Shells |
| 2546' | 2875' | Shale & Lime |
| 2875' | 3085' | Lime |
| 3085' | 3380' | Shale & Lime |
| 3380' | 3558' | Lime |
| 3558' | 3664' | Lime |
| 3664' | 3730' | Lime & Shale |
| 3730' | 3930' | Lime |
| 3930' | T.D. | |

STATE OF KANSAS)

COUNTY OF ELLIS)

I, Leo F. Dreiling, of the L. J. Dreiling & Sons, Inc., upon oath states that the above and foregoing is a true and correct copy from the Daily Drilling Report from your C. Hanna #1.

| | |
|-----------|------|
| TOPS: SMP | |
| Anhydrite | 2021 |
| Heebner | 3698 |
| Toronto | 3722 |
| Lansing | 3738 |
| TD | 3930 |