


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
 508 East Murdock Wichita, Kansas

Company - PRIME DRILLING COMPANY & BROOKS PIERCE
 Farm - Potter No. 1

SEC. 19 T. 11 R. 16W
 CW/2 SE SE

Total Depth. 3385 S.L.M 3381.47
 Comm. 5-10-50 Comp. 6-7-50
 Shot or Treated. Acid 1000
 Contractor. Prime Drilling Co.
 Issued. 9-15-51

County. Ellis
 KANSAS



CASING:

8 5/8" 1033' cem w/500 sx.
 5 1/2" 3376.47 cem w/125 sx.

Elevation. 1838 (sand)

Production. 2 gals. + 50% water

Figures Indicate Bottom of Formations.

shale, post rock 45
 shale, rock 90
 shale, red bed 480
 sand, red bed 595
 iron, sand 610 ✓
 sand 665
 shale, shells, redbed 1025
 anhydrite 1065
 redbed, shale, shells 1390
 salt, shells 1650
 shale, shells 1755
 shab, lime 1955
 lime 2065
 shale, lime 2800
 lime 3385
 Total Depth SLM 3381.47

Tops:

Anhydrite 1025
 Heebner 3015
 Lansing 3063
 Arbuckle 3375

Op. 1/2 hr, rec. 10' oil
 150' OCM