


G. E. Jamison

MARGAY OIL CORP.
Bemis No. 4C.

SEC. 22 T. 11 R.17W
SW SE SW

Total Depth. 3534½'
Comm. 5-6-37 Comp. 6-8-37
Shot or Treated.
Contractor.
Issued. 7-10-37

County. Ellis



CASING:
10" 1272'
7" 3518'

Elevation.

Production. Pot. 2496 B.

Figures Indicate Bottom of Formations.

cellar	10	lime	3020
limestone	20	SIM Corr. 3020-3024	
shale, shells & clay	38	lime	3107
shale & shells	646	lime & brkn lime	3138
sand	664	lime & shale & shells	3173
shale & shells	753	shale blue	3177
black, hrd, sand & lime	840	lime	3226
wtr sand sft white	940	lime & shale	3312
red rock & shale	980	brkn lime	3370
sticky shale & shells	1115	shale	3381
shale & shells	1150	lime white hrd	3393
sand sft hrd	1178	brkn lime	3410
shale & shells	1220	lime hrd	3420
shale blue drk, pyrites	1267	brkn lime	3427
anhydrite	1275	lime	3461
SIM Corr. 1275-1272		lime & shale	3485
anhydrite	1295	lime	3501
anhydrite & shale	1350	lime & sand	3517
anhydrite	1378	lime	3521
shale & shells	1483	SIM Corr. 3521-3518	
red rock, shale & shells	1490	Standard tool meas. 3518-3520	
anhydrite	1510	Siliceous lime 3520-3532	
red rock, shale & shells	1540	lime	3534½
lime shells	1550	Total Depth.	
shale & shells	1807		
anhydrite & lime	1889		
lime & shale	2059		
lime shells hrd	2071		
lime & shale	2165		
lime & shale, red rock	2180		
lime & shale	2337		
lime white med hrd	2369		
lime white sft	2373		
lime white med hrd	2383		
SIM Corr. 2383-2410			
sticky shale	2463		
lime & sticky shale	2504		
lime	2560		
lime & sticky shale	2587		
lime grey, sticky shale blue	2645		
shale & shells sticky	2689		
shale & shells	2805		
shale & shells, sticky shale	2836		
sticky shale & lime shells	2846		
shale & shells	2940		
shale	2946		
lime	2964		
shale & shells	2978		
lime hrd	2998		