
WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
608 E. Murdock Wichita, Kansas

Company: CITIES SERVICE OIL
Farm: COLAHAN "A" No. 29

SEC. 24 T. 11 R. 17W
SE NW NW
990' S & 990' E of NW Cor.

County. Ellis
KANSAS



Elevation. 1919 DF

Production. 156 Oil, tr. wtr/24 hrs.

Total Depth. 3484; PB 3479
Comm. 7-1-50 Comp. 7-14-50
Shot or Treated.
Contractor. Holm Drlg. Co.
Issued. 9-30-50

CASING:
9 5/8" 1120' cem. w/600 sx
7" 3484' cem. w/150 sx

Figures Indicate Bottom of Formations.

shale & lime	50
shale & shells	350
shale, shells & sand	620
iron, shells & shale & sand	795
shale & sand	875
redbed & shells	1000
redbed	1105
anhydrite	1145
shale & shells	1495
salt, shale & shells	1660
shale & shells	1825
shale & limo	2530
shale & shells	2890
limo	3485

3485 RTD = 3484 SLM
Total depth
PB 3479

Tops:

Lansing Corr.	3129
Simpson "	3390
Arbuckle "	3411
Penetration	73'
Total depth	3484

Drilled cement to 3479 SLM
Perf. 12/3452-56½, Fair S.O.
" 30/3452-62, 65' oil in 10 mins.
157' oil in 40 mins.
310' oil in 1 hr. 10 mins.
560' oil in 2 hrs.10 mins.
750' oil in 3 hrs.10 mins.
1040' oil in 4 hrs. 10 mins.
1150' oil in 5 hrs. 10 mins.
1410' oil in 7 hrs. 10 mins.
2320' oil in 18 hrs.40 mins.
Pumped 111 O, 1, 4 water in 12 hrs.