

WELL LOG BUREAU-- KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

Company - CITIES SERVICE OIL CO.
Farm - Colahan "B" No. 16

SEC. 25 T. 11 R. 17W

CWL SW SW
660'N & 330'E of SWc

County. Ellis

KANSAS



Total Depth. 3583'
Comm. 1-7-47 Comp. 2-14-47
Shot or Treated. Acid.
Contractor. Veeder Supply & Development Co.
Issued. 5-10-47

CASING:

8 5/8" 1140' com. w/400 sx.
5 1/2" 3550' com. w/150 sx.

Elevation. 2085 feet

Production. Ech. Pot. 2450 B0
no Wtr. 24 hrs.

Figures Indicate Bottom of Formations.

lime	0-40
shale	195
shale & shells	485
sand & shale	550
shale & shells	760
red bed	785
shale	830
lime sdy	910
sand	990
shale & shells	1075
red bed	1130
shale	1140
red bed	1279
anhydrite	1300
shale & shells	1650
shale	1705
salt	1755
shale & shells	1865
lime & shale	2165
lime	2410
shale & shells	2520
lime & shale	2608
shale & shells	2680
lime & shale	2750
shale & shells	2765
shale	2850
shale & shells	3005
lime & shale	3050
lime	3554
3554 Rot TD = 3552 SLM	
lime	3583
Total Depth	

Tops:

✓ Lansing 3298
✓ Corr. Top Simpson 3534
✓ Corr. " Arbuckle 3549

Penetration 34'

Fillup: 2090' oil in 9 hrs. at
3558-2610 Oil in 10 3/4 hrs.
@ 3558

After 1500 acid @ T.D. 3558, Pumped
119 Oil, no wtr., 14 hrs.

Deepened 3558-83.

7 7/8" Rotary Hole.