

KANSAS WELL LOG BUREAU --- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

COMPANY CITIES SERVICE OIL CO.


SEC. 25 T. 11 R. 17W

FARM Colahan "B" NO. 20

LOC. SE NE NW
990' S, 330' W of N/4 cor.

TOTAL DEPTH 2520 SLM PB 3514
 COMM. 10-5-50 COMP. 10-16-50
 SHOT OR TREATED 250 gals.
 CONTRACTOR Holm Drlg Co.
 ISSUED 1-20-51

COUNTY Ellis



CASING
 8 5/8" 1156' cem w/500 sx.
 5 1/2" 3220' cem w/150 sx.

ELEVATION 1959 (1957 Gr.)

PRODUCTION Phy. Pot. 40 bbls oil
28 water

FIGURES INDICATE BOTTOM OF FORMATIONS

lime	50
shale, shells	565
sand, shale, shells	715
sand	795
iron, shale	810 ✓
shale, shells	865
red bed	900
red bed, shale	1140
anhydrite	1180
shale, shells	1530
salt, shale, shells	1725
shale, shells	1750
lime, shale	2545
shale, shells	2915
lime, shale	2950
lime	3520
3520 RTD = 3520 SLM	
Total Depth	

Tops:

Lansing	3171
Simpson	3439
Arbuckle	3453
Penetration	67

Drilled cement to 3514 SLM.

Perf. 13 shots 3496-99.

315' oil and 100' water
in 13 hrs.

7 7/8" rotary hole.