


DEEP ROCK OIL CORP.
Baumer No. 9

SEC. 27 T. 11 R. 17W.
SE NW NW
990' fr NL 990' fr WL

Total Depth. 3464
Comm. ~~6-13-37~~ Comp. 7-6-37
Shot or Treated.
Contractor. Glem Drlg. Co.
Issued. 10-2-37

OCT 2 1937

County. Ellis.



CASING.

15 $\frac{1}{2}$ " 50'
10" 1200'
7" 3455'

Elevation

Production. Pot. 2420 B.

Figures Indicate Bottom of Formations.

cellar	8
shale	50
shale and shells	710
shale shells and iron	920 ✓
shale shells and red bed	1130
shale shells & iron	1196 ✓
anhydrite	1203
anhydrite	1240
shale and lime	1395
shale and shells	1617
salt and shale	1815
shale and lime	1920
lime broken	1980
shale and shells	2025
lime	2300
broken lime	2350
shale and shells	2370
lime	2400
shale and shells	2410
lime	2560
shale and shells	2611
lime	2700
broken lime	2725
shale and lime	2780
shale	2910
lime Topeka	3185
lime K.C.	3445
sand Simpson	3450
lime siliceous oil	3464
Total Depth.	
Top Anhydrite	1195
Top Neva lime	2365
Top Tarkio	2710
show oil saturation	2940-2950
Top Topeka lime	3008
show oil saturation	3110-3125
show oil saturation	3180-3190
Top Lansing K.C.	3270
show oil saturation	3300-3310
show oil saturation	3350-3360
show oilsaturation	3370-3385
Simpson sand Oil sat.	3445-3450
cored	3450-3457
siliceous lime	3454-3464
good sat. 3454-57	

siliceous lime and dolomite 3454-3464 Pay