
WELL LOG BUREAU -- KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

Company. THE TEXAS CO.
Farm. F.A.Bemis "A" No. 14

SEC. 28 T. 11 R. 17W
SE SW NE

Total Depth. 3646'PB to 3492'
Comm. 5-15-47 Comp. 6-23-47
Shot or Treated.
Contractor. Kiowa Drlg. Co.
Issued. 9-6-47

County. Ellis
KANSAS



Elevation. 1976 sd Kb.

CASING:
8 5/8" 1216' cem. w/550 sx.
5½" 3643' cem. w/175 sx.

Production. Pmpg.417 Bbls.Oil
10% wtr.

Figures Indicate Bottom of Formations.

surface clay	40
clay & shale	530
sand	650
sand & iron	860
shale,shells & iron	900
shale & red bed	1160
red bed	1201
anhydrite	1240
sand	1260
red bed	1365
shale	1565
salt	1675
shale & shells	1840
shale & lime	2100
lime & shale	2320
shale & shells	2420
shale & lime	2525
shale & shells	2660
shale & lime	2885
shale & shells	2910
lime & shells	2950
lime	3005
lime & shale	3070
lime	3155
lime & shale	3205
lime	3646

Total Depth(PB to 3492')

Tops:

Anhydrite	1201
Heebner	3143
Lansing	3215
Simpson	3448
Arbuckle	3473

REMARKS:

6-11-47 Perf. 3632-39 no show.
6-12-47 Plug back to 3640.
6-13-47 Plug back to 3620.
6-14-47 Perf. 3602-13 w/8 shots, billed up w/2000 water in 1 hr.
6-15-47 Plugged back to 3594. perf. 3578-86 w/8 shots, 3578-80 w/3 shots, tested one bailer wtr. per hr., no show. Perf. 3580-86 w/5 shots,tested 3 bailers wtr. per hr., no show.
6-16-47 Plug back to 3570.
6-18-47 Perf. 3555-65 w/15,perf. 3560-65, 1½ bailer wtr. per hr. perf. 3540-48 w/8 shot, filled up 2000' wtr. in 5 hrs. Plug back to 3536.
6-19-47 Perf. 3525-34 w/10 shot. ½ bailer wtr. per hr. for 4 hrs.
6-21-47 Perf. 3495-3506 w/1 shot per ft. Perf. 3506-10 w/35 shots, S.S. oil. Perf. 3468-70 w/3 shots, 2/3 bbl. oil, 4 gal. wtr. per. hr.
6-22-47 Plug back to 3510-3492 w/3 sax. Perf. 3470-74 w/4 shots, no show. Perf. 3474-78 w/4 shots, filled up 500' oil, no wtr.
6-23-47 Perf.3468-78 w/4 shots per fcot, filled up 1500' oil in one hour.