

ANDERSON-PRICHARD OIL CORP.  
Samuelson No. 1.

SEC. 36 T. 11 R. 17 W  
NWc NW

Total Depth. 3605'  
Comm. 4-12-43 Comp. 5-25-43  
Shot or Treated.  
Contractor. Uscan Drlg. Co.  
Issued. 7-31-43

County. Ellis



CASING:  
12 1/2" 80'  
8 1/4" 1296'  
5 1/2" 3596'

Elevation.

Production. Temp. Pot. 73 B.  
No wtr

Figures Indicate Bottom of Formations.

shells	90
shale	390
shale-shells-iron	
pyrites	843 ✓
iron pyrites	849 ✓
shale & shells	860
sand & shale	920
shale & shells	1040
shale gy	1100
red rock	1185
red bed & shale	1285
anhydrite-gyp	1310
lime	1325
shale	1370
red rock & shale	1455
red rock & shale gy	1610
shale	1660
salt & shale	1805
shale	1895
lime	1950
shells & shale	1980
lime brkn	2010
lime	2050
shale & shells	2145
lime & shale	2215
lime	2250
shells	2275
lime & shale	2355
lime	2575
lime & shale	2830
shale	2860
lime	2900
lime & shale	2947
shale	3015
lime & shale	3038
lime	3580
chert	3585
dolomite	3605
Total Depth.	

Tops: Anhy.	1285
Lansing	3317
Ero. Arb.	3582
Solid Arb.	3597