

13-11-18W

DARBY PETROLEUM CORP.
Peavey "A" No. 7

SEC. 13 T. 11 R. 18W.
CEL SW SW

Total Depth. 3425
Comm. 5-18-41 Comp. 6-1-41
Shot or Treated. 500 gal acid.
Contractor.
Issued. 6-28-41

County Ellis.



CASING.

15" 112'
10" 1189'
7" 3416'

Elevation.

Production. Pot. 3000B.
Maximum

Figures Indicate Bottom of Formations.

shale and sand	122
shale and shells	260
shale shells and sand	
and iron	579 ✓
iron shale and sand	710 ✓
sand	853
shale and shells	1182
anhydrite	1193
lime and shale	1530
shale and salt	1790
shale and shells	1885
shale and lime	2165
lime	2235
lime and shale	2415
shale	2575
shale and lime	2640
shale	2750
shale and lime	2915
lime	3220
lime and shale	3345
lime	3400
dolomite	3425
Total Depth.	

Top of Simpson 3404
Simpson shale 3407
Simpson sand 3415 Saturated.
Arbuckle 3415 CTD.

Saturation 3413
Saturated dolo. 3416.
RUST and drilling cement 3420
1500' OIH in 45 Min.
2750' OIH 2 hours.
Drilling deeper 3425 TD.