Company. G. T. KEYES DRILLING CO. et al, SEC. 25 T. 11 R. 18W
Farm. Marshall No. 2 NW NE NW

Total Depth. 3474
Comm. 8-10-47 Comp. 9-6-47
Shot or Treated.
Contractor.
Issued. 10-18-47

County. Ellis
KANSAS

Elevation. 1935 est + rb

Production. Pot. 2963

CASING:
8-5/8" 1195'
5-1/2" 3467½' DFM

Figures Indicate Bottom of Formations.

clay, shale & shells	230
shale and shells	360
white sand	390
shale and shells	475
sand and shale	580
pyrite	620
sand and shells	680
sand, shale and shells	835
shale and shells	940
shale, shells & red bed	1100
redbed & shells	1180
anhydrite	1220
shale & shells	1620
salt, shale& shells	1795
lime and shale	1985
broken lime, shale and shells	2115
broken lime	2220
shale & shells	2365
lime & shale	2450
lime	2600
shale & shells	2875
lime	3105
shale & lime	3155
lime	3385
lime and shale	3415
conglomerate	3430
simpson	3470
lime	3471
Total Rotary Depth	3471

Cable Tool Work
Moved in cable tools, cleaned out drilled cem. and drilled deeper.
3471 to 3474 lime
3474 Total Depth

TOPS: corrected 3' to derrick floor

Heebner shale	3111
Lansing	3156
Marmaton	3412
Simpson shale	3441
Simpson Dol.	3449
Arbuckle	3467