

Albert J. Hume


CHAMPLIN REFG. CO.
Meier No. 1.

SEC. 36 T. 11 R. 18W.
NE 1/4 SW
330' S of NL. 250' W of EL SW 1/4

Total Depth. 3625
Comm. 12-2-36 Comp. 12-31-36
Shot or Treated.
Contractor.
Issued. 2-6-37

County. Ellis.

FEB 6 1937



CASING.
15 1/2" 16'
10" 1349'
7" 3585'

Elevation.

Production. Pot. 679 B.
in 20 hours.

Figures Indicate Bottom of Formations.

surface sand and rock	45
shale blue	140
shale blue soft	235
shale blue & hard sand	345
shale blue	351
shale and hard sand	392
shale and sand	450
lime hard	460
shale	474
shale & hard sand	559
shale	590
water sand	680
shale	700
shale and shells	845
water sand	990
sand and shale	1061
shale and shells	1108
red rock	1150
shale and shells	1182
red rock & shells	1335
anhydrite	1342
anhydrite	1372
red rock	1400
red rock and shells	1445
red rock	1560
sdv shale	1578
red rock and sand	1599
red rock and iron	1632
red rock and shale	1675
sdv shale	1805
shale blue and red	1890
shale and lime shells	1935
lime hard	1962
lime broken	2847
shale and lime	2869
sticky shale	2899
broken lime	2927
shale blue & lime shells	3050
shale and shells	3110
broken lime	3390
Oswald lime	3443
broken lime	3489
lime	3587
shale red and blue	3597
lime	3611
shale green & dolomite	3625
Total Depth.	

SAMPLE TOPS.

Top Anhydrite	1330
Top Topeka	3050
Top Oswald	3340
Top Simpson	3592
Top Arbuckle	3623
Base Pennsylvanian	3580

Prod. 1st 24 hrs. 150 bbls