WELL LOG BUREAU — KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

Company. BRIDGEPORT OIL CO.,INC.
Farm. Sessin "A" No. 1-A.


SEC. 15 T. 11 R. 19 W
SE SW SE

Total Depth. 3507' PB 3233'
Comm. 11-1-44 Comp. 12-9-44
Shot or Treated.
Contractor.
Issued. 12-30-44

Rotary 0-3462
Cable 3462-3507

CASING:
8 5/8" 1240' Cem.
5 1/2" 3454' Cem.

County. Ellis
KANSAS



Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

shale	142
shale & shells	585
sand	810
shale blue & shells	875
sand & shells	995
sand & shale	1084
shale & red rock	1230
gyp & anhydrite	1240
anhydrite	1275
red rock & shale	1530
shale sdy	1673
shale & shells	1795
lime	1827
shale & lime shells	1835
shale & shells	2034
lime	2087
lime brkn	2165
lime	2260
lime sdy	2281
lime	2381
lime sdy	2482
lime	2538
shale & lime shells	2629
shale sft & lime	2700
shale & lime shells	2820
shale	2901
lime	2950
lime & shale	3010
lime hrd	3027
lime	3070
shale & lime shells	3111
lime & shale	3139
lime	3221
lime (KC)	3259
lime	3395
shale & lime streaks	3424
shale	3462
chert & brown dolomite	3463
lime	3507
Total Depth	

Tops:

Topeka	2901
Heebner	3113
Toronto	3130
Base Oread	3138
Lansing	3142
Base Kans City	3396
Simpson	3448
Arbuckle	3453

At 3463 tested 5 gal.oil in 2 hrs
Perf. formation 36 shots 3454-63, no increase
Gravity 22.2
Acidized 1000 gals.acid & 500 gals.Butane
Maximum pressure of 1300 lbs., broke to 650 & unable to increase pressure pumping full capacity. Swbd 1 BOPH
Acidized w/1000 gals.Butane, 3000 gals.acid
Maximum pressure 900 lbs, dropped to 650. Swbd 143 B.in 22 hrs, sample ground out 24% wtr. At end of swbd test, well swbg approx. 5 BPH. Ran bailer, rec.2 BW
Deepened to 3507, approx. 1400' of fluid, of which 400' was wtr
Plugged back to 3233 w/Lane-Wells Plug.
Perf. from 3172-97, no shows
Perf. from 2914-26
Acidized thru perforations 3172-97 w/350 gals.& thru perforations 2914-26 w/650 gals.
After acidizing, swbd 1 BWPH, no oil