

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY

508 East Murdock,

Wichita, Kansas

Company- SKELLY OIL CO.

Farm- Vine "C"

No. 3

Teresa Vine 'C' (PRL 10-11-06)

SEC. 27

T. 11

R. 19W

NE NE SE

330' fr NL 330' fr EL

Total Depth. 3572

Comm. 6-15-53

Comp. 7-1-53


Shot or Treated.

Contractor. Wentworth Drilling Co., Inc.

Issued. 8-15-53

County Ellis

KANSAS



CASING:

8 5/8 @ 1357' w/ 500 sx cem.

5 1/2 @ 3559' w/ 300 sx cem.

Elevation. 2050 DF

Production. Pot. 109 B0

Figures indicate Bottom of Formations.

rock & sand	150
shale	320
shale & shells	620
shale & sand	1060
shale	1140
shale & shells	1347
anhydrite	1580
shale & salt	1850
shale	2115
shale & lime	2215
shale	2450
shale & lime	2615
shale	2695
shale & lime	3035
shale & shells	3115
lime & shale	3195
lime	3530
chert	3533
sand	3542
lime	3558
dolomite	3566
dolomite & shale	3570
dolomite	3572
Total Depth	

TOPS

Anhydrite	1344
Heebner	3227
Toronto	3252
Lansing	3270
Conglomerate	3510
Simpson sand	3545
Arbuckle	3561

850' OIH/ 8 hrs. 1500' OIH/ 15 hrs.

Ran Lane-Wells Gamma Ray Survey

2800' OIH, static level 1700'

Prod. form. Arbuckle lime 3561-3572