


*Plotted*

DARBY PETROLEUM CORP.  
Findlay No. 1

SEC. 23 T. 11 R. 21 W.  
SE NW NW

Total Depth. 3990  
Comm. 6-15-42 Comp. 7-2-42  
Shot or Treated.  
Contractor.  
Issued. 10-3-42

County Trego.



CASING.

10" 156'

Elevation.

Production. Dry.

Figures Indicate Bottom of Formations.

|                       |      |
|-----------------------|------|
| shale                 | 40   |
| sand                  | 150  |
| shale and shells      | 254  |
| sand and shale        | 745  |
| shale and shells      | 875  |
| sand and iron         | 1210 |
| sand                  | 1425 |
| red bed and shale     | 1740 |
| anhydrite             | 1780 |
| shale and shells      | 2155 |
| salt and shale        | 2230 |
| shale and lime        | 2510 |
| shale                 | 2520 |
| shale and lime        | 2585 |
| shale                 | 2665 |
| shale and lime        | 2710 |
| shale and broken lime | 2835 |
| shale and lime        | 2853 |
| sand                  | 2920 |
| shale and lime        | 3382 |
| lime                  | 3990 |

Total Depth.

Slight porosity with spotted  
oil stains at T.D.

Top Lansing 3584  
Top Arbuckle 3920 CTD.

Stone Corall Anhydrite 1735 CTD  
Ft. Riley lime 2490  
Neva lime 2850  
Topeka lime 3350