

10-11-23W

OPERATOR:
CONTRACTOR:
WELL NAME:
LOCATION:

GEOLOGIST:
SPUD DATE:
COMPLETION DATE:

John P. Jennings
Abercrombie Drilling, Inc.
GALLOWAY #1
C W/2 SW/4 Sec. 10-11S-23W
Trego County, Kansas
Don Strong
November 13, 1975
November 20, 1975

0	80	Soil, Clay & Sand
80	745	Shale
745	840	Sand
840	985	Shale
985	1050	Sand
1050	1250	Shale
1250	1475	Sand
1475	1734	Shale
1734	1774	Anhydrite
1774	2260	Shale
2260	3363	Lime and Shale
3363	3493	Lime
3493	3537	Lime & Shale
3537	3734	Lime
	3734	Rotary Total Depth

Drilled 208' of 12¼" hole. Ran 5 jts. of 8 5/8" casing, Set @ 205.90' K.B. Cemented with 165 sx. Quick-Set cement. Cement did circulate. Plug was down @ 4:00 p.m. November 13, 1975.

Plugged and Abandoned: 1st Plug was set @ 900' with 70 sx. cement; 2nd Plug was set @ 200' with 20 sx. cement; 3rd Plug was set @ 40' with 10 sx. cement. State Plugger: Gilbert Balthazor P. was down @ 3:00 a.m. November 20, 1975.

SAMPLE TOPS:

Anhydrite 1734
B/Anhydrite 1774

STATE OF KANSAS)
) SS
COUNTY OF SEDGWICK)

Jerry A. Langrehr, Executive Vice President of Abercrombie Drilling, Inc., does hereby state that the above and foregoing is a true and correct copy of the log of the GALLOWAY #1, C W/2 SW/4 Section 10-11S-23W, Trego County, Kansas.