

96653

SIDE TWO

Operator Name Vanmax Exploration..... Lease Name HINSHAW..... Well# ...1 SEC.36... TWP.11S...RGE.23..... East West

WELL LOG

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all drill stem tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log.

Drill Stem Tests Taken Yes No
 Samples Sent to Geological Survey Yes No
 Cores Taken Yes No

Formation Description
 Log Sample

Name Top Bottom

	LOG	SAMPLES		
ANHYDRITE	1854 (+ 566)	1857 (+ 563)		
TOPEKA	3420 (-1000)	3426 (-1006)		
HEFBNER	3637 (-1217)	3645 (-1225)		
TORONTO	3660 (-1240)	3664 (-1244)		
LANSING/K.C. "A"	3674 (-1254)	3682 (-1262)	36	
LANSING/K.C. "J"	3848 (-1428)	3855 (-1438)		
HERTHA	3940 (-1520)	3951 (-1531)		
MARMATON	4000 (-1580)	4008 (-1588)		
ARBUCKLE	4088 (-1668)	4097 (-1677)		
TOTAL DEPTH	4146 (-1726)	4152 (-1732)		

TUBING RECORD size 2" set at 4014 packer at _____ Liner Run Yes No

Date of First Production 7-17-84 Producing method flowing pumping gas lift Other (explain) _____

Estimated Production Per 24 Hours	Oil	Gas	Water	Gas-Oil Ratio	Gravity
25	none	5	none	33	
	Bbls	MCF	Bbls	CFPB	

METHOD OF COMPLETION

PRODUCTION INTERVAL

Disposition of gas: vented open hole perforation
 sold other (specify) _____

4012-4024 & 4028-4042

CASING RECORD new used

Report all strings set - conductor, surface, intermediate, production, etc.

Purpose of string	size hole drilled	size casing set (in O.D.)	weight lbs/ft.	setting depth	type of cement	# sacks used	type and percent additives
Surface Production	12 1/4" 7 7/8"	8 5/8" 4 1/2"	20# 10 1/2#	410.33' 4124.43'	Common EAZ Flocheck 2	270 125 300 gal	2% gel, 3% c.c. .75% CFR-2

PERFORATION RECORD

Acid, Fracture, Shot, Cement Squeeze Record

shots per foot	specify footage of each interval perforated	(amount and kind of material used)	Depth
2	4012 - 4024 & 4028 - 4042	1500 gallon of mud acid 33,700 sand with 752.4 barrel of Gel Fluid into perforations	