


Total Depth. 5270'
 Comm. 9-29-37 Comp. 11-3-37
 Shot or Treated.
 Contractor, Holmerich & Payne
 Issued. 11-27-37

County. Wallace



CASING:
 12 $\frac{1}{2}$ " 165'

Elevation. 3662

Production. Dry

Figures Indicate Bottom of Formations.

surface	18	shale	3820
shale	185	lime	3895
sand	250	shale	3960
shells	280	lime	3985
shale	410	shale	3990
shale & shells	785	lime	4025
shale	1535	sdv lime	4030
lime	1590	lime	4055
shale	1790	shale	4070
lime	1810	brkn sand	4080
shale & bentonite	1856	slight smell of gas	
shale	2000	lime	4205
sand	2030	shale yellow	4215
shale	2060	lime	4286
lime	2070	brkn lime	4415
brkn lime	2145	lime	4558
sand brkn	2165	Cored 4225-4235	
brkn lime	2190	brkn lime	4600
sdv lime hrd	2240	lime hrd	4625
shale	2330	lime	4710
sand	2360	lime hrd	4722
shale	2400	lime	4929
lime	2420	lime hrd	4965
shale	2460	lime	5032
lime	2480	shale green & blk	5062
shale	2500	shale & lime shells	5090
brkn sand	2520	shale, sand & lime	5103
shale & lime shells	2594	sand	5108
brkn lime	2720	lime hrd	5145
sand	2745	shale	5153
lime	2755	lime	5156
red beds	2940	shale & lime	5185
lime	2980	brkn lime	5237
shale	2995	sdv lime	5250
conglomerate	3050	sand hrd & lime	5266
sdv lime, shale strks	3120	sdv lime	5270
shale	3210	Total Depth.	
sdv shale	3250		
shale & lime shells	3323		
brkn lime	3385		
lime	3410		
sand & shale	3435		
lime	3482		
sdv lime	3502		
lime	3550		
sand	3580		
shale	3590		
shale yellow	3610		
lime	3622		
lime & shale yellow	3640		
lime	3690		
shale	3725		
lime	3735		
shale	3750		
sdv lime	3770		
sand	3775		
lime	3795		