KANSAS WELL LOG BUREAU -- KANSAS GEOLOGICAL SOCIETY

UNION NATIONAL BANK BLDG, WICHITA, KANSAS

Pickrell Texas Co.

Location. NE c NW SW Sec. 17 T. 12 R. 15W.


DEEPENING RECORD

Casing Record.

10"1562
20" 10 8¼" 2465
15½"447 65/8"3017
12½"932 53/16"
Total Depth. 3330'

Farm. E.C.Munsell "A" No. 2
Company. Wilcox Oil and Gas Co.
Contr. Stearns and Streetor
Comm. 4-15-26 Comp.6-9-26
Shot quarts Between.

County. Russell



Elevation.

Figures Indicate Bottom of Formations.
Date Issued. 4-10-46

Initial Production.
1st 24 hrs. 120 bbls.,
2nd 24 hrs. 144 bbls.

Formation		Depth
yellow clay soft		33
shale blue soft		205
shale grey soft		260
red rock soft		275
shale grey soft		300
sdy shale	HFW 300	335
sand light soft		390
shale brown soft		415
sand brown soft		440
lime white hard		445
shale blue soft	HFW 480	480
sand blue soft		510
shale blue soft		520
slate blue		540
slate blue soft		550
shale blk soft		560
shale dark soft		565
talc white soft		585
red rock soft		600
shale grey soft		608
shale grey Sandy		618
red rock soft		929
chalk white soft		931
lime white hard		975
red rock soft		1080
slate blue soft		1122
lime dark hard		1124
shale grey soft		1160
red rock soft		1206
slate blue soft		1270
salt		1556
shale blue soft		1561
lime white hard		1565
shale blue soft		1590
lime white hard		1600
slate grey soft		1610
lime white hard		1640
shale white soft		1645
lime white hard		1690
red rock soft		1710
lime white hard		1730
shale brown soft		1736
shale blue soft		1741
lime white hard		1792
red rock		1820
lime white hard		1845
shale green soft		1856
lime white hard		1925
shale grey soft		1935
red rock soft		1945
lime white hard		1965
shale grey soft		1975
lime white hard		2000
shale blue soft		2010
red rock		2022
lime white hard		2130
red rock soft		2160
lime white hard		2185
shale blue soft		2195
lime white hard		2210
shale blue soft		2225

Formation		Depth.
lime white hard		2235
shale blk soft		2245
shale grey soft		2345
slate white soft		2350
shale blue soft		2390
red shale soft		2415
shale blue soft		2465
sdy shale soft		2505
lime white hard		2515
shale grey soft		2550
lime white hard		2555
shale blue soft		2580
lime white hard		2590
shale white soft		2595
lime white hard		2615
shale blue soft		2636
lime white hard		2640
shale blue soft		2690
lime white hard		2706
slate blue soft		2709
slate blue		2739
shale blue soft		2741
lime white hard		2762
shale blue soft		2769
slate blue		2776
lime		2785
slate		2790
lime		2800
lime white hard		2810
shale light soft		2835
lime light hard		2850
lime		2875
lime white hard		2905
lime		2920
slate grey		2930
broken lime		2935
LBW 2930		
slate		2970
lime white hard		2983
shale blue soft		2997
Dodge lime hard		3010
shale blue soft	SLM	3015
shale blue soft		3017
lime oil pay		3029 TD

Both top pay and bottom hole are SLM
15½ UR 548

DEEPENING RECORD

Old T.D.		3029
Comm. 10-13-26	Comp. 10-17-26	
No production available		
sdy lime 3029-		3033
shale		3036
sdy lime		3051
lime		3067 TD

(OVER)

Sohio Petro.Co. #2 Munsell "A" NE NW SW Sec.17-12-15W 96129
96856

DEEPENING RECORD:

Comm.4-23-47 Comp.5-21-47
Prod. 25 BOPD & trace wtr

OTD 3067; Lansing 3017
S.O. 3234; clean out 3238
lime? 3309
ran 326' 5½" liner
@3290 W.O.C. 5-7-47
cement 5-14-47
DP & DD 5-21-47
chty cong. 3311-3330
Total Depth.

S.S. dead oil 3328-30
P. B. 3259
Perf. 45 @ 3228-44
1000 A.; S.W. down
400' O. no time
5-28-47 3000 A.
25 BOPD & trace wtr