

CENTRAL PETROLEUM CO.
Rusch "B" No. 3,

Plotted Texas CO.
SEC. 19 T. 12 R. 15W
Center SL NE SW

DEEPENING RECORD

Total Depth. 3137'
Comm. 8-4-36 Comp. 9-2-36
Shot or Treated.
Contractor, Harry Gore
Issued. 4-7-45

County. Russell

CASING:
15 1/8" 335'
12 1/8" 575'
10 " 960' Left in
8 1/4" 2510' UR 2700'
6 5/8" 2938' Left in
5 3/16" Linor 116' set at 3025'



Elevation.

Production. Pot. 538 B.

Figures Indicate Bottom of Formations.

soil	10	lime	1853	shale dark	2718
clay	40	shale blue	1866	limo	2740
slate blue	210	lime brkn	1880	shale	2750
shale light	280	lime hrd	1935	lime hrd	2752
shale red	300	red rock	1950	lime sft (sh oil)	2755
shale yellow	305	lime	1970	limo	2775
shale blue	310	red rock	1985	shale	2780
shale light	330	lime	2010	limo	2835
sand white (HFV 330-35)	335	shale brown	2035	shale	2840
red rock	400	lime	2050	limo	2882
water sand	420	shale blue	2055	slate	2888
shale light	465	lime	2100	limo	2935
slate blue	480	shale blue	2105	shale blue	2938
shale blue	510	lime (SEPH 2755-65)	2135	lime	2978
sand sft	515	red rock	2155	shale black	2980
shale blue	535	lime	2215	lime white hrd	2989
sand	540	shale blue	2225	shale blue	2998
gumbo blue	550	lime	2243	lime white	3011
shale blue (HFV 580-95)	580	shale blue	2245	shale blue	3015
water sand	595	lime	2290	shale brown	3020
lime	605	shale blue	2305	shale green	3025
red rock	957	lime	2315	limo	3045
lime anhydrite	982	shale & sholls	2325	Top Oswald 3025	
shale blue	985	lime	2340	shale blue	3051
red rock	1105	shale & shells	2370	lime	3085
shale blue	1155	shale blue	2380	Total Depth.	
red rock	1240	lime	2390		
shale blue	1285	shale blue	2405		
salt	1585	shale & sholls	2500		
shale & shells	1600	lime	2520		
lime	1605	Gas 2445-2465			
shale blue	1620	shale	2525	Dodge Lime	2957-61
lime	1628	lime	2530	Oswald Lime	3030-35 Pay
shale	1640	shale blue	2552	Oswald Lime	3052-82 Pay
broken lime	1660	lime	2560		2752-55 Sh oil
shale blue	1665	shale & sholls	2565		2445-65 Gas
lime	1673	lime	2575		
shale light	1680	shale	2578		
lime	1700	lime	2598		
red rock	1707	shale light	2606		
lime	1710	lime	2620		
red rock	1725	shale blue	2627		
lime	1735	lime	2650		
shale & shells	1770	shale	2665		
lime	1792	lime sft	2675		
red rock	1800	lime (SEPH 2665-75)	2680		
lime	1805	shale	2695		
red rock	1825	lime	2710		

SAND RECORD

Dodge Lime	2957-61
Oswald Lime	3030-35 Pay
Oswald Lime	3052-82 Pay
	2752-55 Sh oil
	2445-65 Gas

4 1/2 B of Oil Per Hr 2957-61

DEEPENING RECORD:

Comm. 8-29-43
Comp. 12-6-44
Est. Pot. 150 B.
Top Topoka 3016
lime 3120
11 gal. wtr PH 3120
shale 3123
lime hd 3130
lime softer 3135
lime sft 3137
1600' fluid 3135
Total Depth.

Over

P1

Central Petroleum Company, Inc.
Tulsa, Oklahoma

APR - 4

State Geological Survey
WICHITA BRANCH
19-12-15W

NATHAN APPLEMAN, PRESIDENT
A. J. LEWIS, VICE-PRESIDENT
F. W. SIMMS, ASSISTANT SECRETARY

August 8, 1939

Deepening Report of Rusch B # 3

Deepened from 3085' to 3108'

Cleaned out 12' of Cavings.

3085-3090	Lime hard
3090-3094	Lime hard
3094-3098	Lime hard
3098-3100	Lime hard
3100-3104	Lime soft (Pay)
3104-3105	Lime soft (Pay)
3105-3108	Lime hard
3108	Total Depth August 8, 1939

Central Petroleum Co., Inc.

By C. H. Gilbert
Supt.

RECEIVED
STATE CORPORATION COMMISSION

APR 02 1985

CONSERVATION DIVISION
Wichita, Kansas