
Willie E. Schultz, being of lawful age, hereby certifies
that:

SIDE TWO

Inc.

ACO-1 WELL HISTORY

OPERATOR Isern-Schultz Oil & Gas, LEASE Harold Schmeidler SEC. 33 TWP. 12 RGE. 17 (W)

FILL IN WELL INFORMATION AS REQUIRED:

WELL NO. 2

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
☒ Check if no Drill Stem Tests Run.				
☐ Check if samples sent to Geological Survey				
Top Soil & Sand	0'	40'		
Shale	40'	267'		
Sand & Shale	267'	454'		
Shale	454'	770'		
Sand	770'	920'		
Shale	920'	1141'		
Red Bed & Shale	1141'	1281'		
Anhy.	1281'	1327'		
Shale	1327'	1556'		
Shale	1556'	1930'		
Shale & Lime	1930'	2090'		
Lime	2090'	2233'		
Lime & Shale	2233'	2440'		
Shale & Lime	2440'	2600'		
Lime & Shale Streaks	2600'	2788'		
Shale	2788'	2960'		
Lime	2960'	3195'		
Lime & Shale	3195'	3293'		
Lime	3293'	3383'		
Lime	3383'	3475'		
Lime	3475'	3564'		
Lime	3564'	3636'		
T.D.	3636'			

If additional space is needed use Page 2,

Report of all strings set—surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
	12 1/4"	8 5/8"		262'	sunset	150	

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
TUBING RECORD					
Size	Setting depth	Packer set at			