

CARTER OIL CO.
A.V. Staab No. 3.

DEEPENING RECORD

SEC. 11 T. 12 R. 18W
SEo NW
330' fr S & E L. E $\frac{1}{2}$ NW
SE SE NW
County. Ellis

Total Depth. 3671'
Comm. 5-12-37 Comp. 6-9-37
Shot or Treated. 1500 Gals. 3649-3655
Contractor. Robey Drlg. Co.
Issued. 7-28-45 Rotary 3655



Elevation.

CASING:
10" 1377'
7" 3648'

Production. Pot. 1002 B.
No wtr.

Figures Indicate Bottom of Formations.

cellar	8		
clay	15		
shale, shells	630		
shale	865		
lime	885	Shots	Location
sand	1035	12	3470-74 $\frac{1}{2}$ ' no sho
sand hrd	1080	12	3475-80 $\frac{1}{2}$ ' no sho
sand	1145	12	3481-86 $\frac{1}{2}$ ' no sho
red bed, shells	1364	7	3487-90' no sho
anhydrite	1378	12	3434 $\frac{1}{2}$ -40' no sho
lime	1390		
anhydrite	1425		
red bed, shells	1500		
red rock, salt	1670		
salt	1855		
salt, shale	1965		
lime, shale	2000		
lime	2590		
lime brkn	2660		
lime	2733		
lime, shale, shells	2805		
lime brkn	2854		
shale, shells	2970		
lime	2996		
shale, shells	3060		
shale	3070		
lime	3157		
brkn lime	3200		
lime	3225		
dolomitic lime	3240		
lime hrd	3274		
lime	3405		
lime brkn	3410		
shale	3415		
brkn lime	3420		
lime	3606		
shale red	3625		
lime	3650		
lime cored	3655		
Total Depth.			

4-26-45 - Run bailer as final check - no oil recovered.

B. Plug back & test K.C. lime. 4-25-45 Set Lane-Wells plug @ 3530'. Place 2' of rock on top of plug. Perforate (Lane-Wells)

Siliceous lime 3649-3655
Topeka Top 3070

DEEPENING RECORD:

T. D. - 3671'
I. P. - Dry
Comm. - 4-1-45
Comp. - 4-3-45

Testing Program

4. Drill deeper to test Arbuckle lime 4-1,2,3,-45 Drill (Cable tools) 3655' to 3671' (Arbuckle).
4-5-45 Acidize w/1500 gals.
4-14-45 Test: 5.35 BO, 48.21
B.B. per 24 hrs.