

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
 508 East Murdock, Wichita, Kansas

Company- SKELLY OIL CO.
 Farm- J.G. Dinkel No. 3


SEC. 13 T. 12 R.18W
 SE NW NE

4294 FSL and 1650 FEL-LEO Web 11/28/2022

Total Depth. 3705' PB 3676' DEEPENING RECORD:
 Comm. 2-1-51 Comp. 3-1-51
 Shot or Treated.
 Contractor. Claude Wentworth Drlg. Co., Inc.
 Issued. 8-9-58

County Ellis

KANSAS



Elevation. 2161' DE

Production. 103 BOPD & 106 BW

CASING:

8 5/8" 802'6" w/575 sx cem.
 5 1/2" 1932'4" w/200 sx cem.

Figures Indicate Bottom of Formations.

surface soil, sandstone	110	3670'-3675 1/2' w/500 gals. acid
sand	135	10-18-56
shells, shale	675	ACID TREATMENT No. 3 - Between
sand	775	3 670' - 3675 1/2' w/2500 gals.
shale, shells	920	19-19-56
sand	1050	
shale, shells	1403	
anhydrite	1413	
Reamed 9 7/8" hole to 12 1/4"		
anhydrite	1442	
shale, shells	1800	
sand	1820	
salt, sand	1905	
shale	1990	
shale, lime	3160	
lime	3200	
lime, shale	3255	
lime	3490	
lime, shale	3500	
sdv lime	3520	
lime	3652	
shale	3676	
fine to med. xlyn dolomite	3679	
hrd light gry, finely xlyn. dolomite	3681	
Med. doft, light gry coarsely xlyn dolomite	3683	
Total Depth		
PB	3681	

TOPS:

Anhydrite	1403
Heebner shale	3363
Toronto lime	3382
Lansing lime	3405
Simpson shale	3662
Arbuckle lime	3676

ACID TREATMENT: No. 1 Between
 3677-3681' 3-7-51--w/200 gals.

DEEPENING RECORD:

Comm.-10-12-56
 Comp.-10-22-56
 Prod.- 87 BO & 57 BW POB 24 hrs.
 O.T.D. 3681'
 Plastic w/white & tan xlyn dolomite 3683
 White to brown xlyn dolomite 3686
 same 3688
 white to tan dolomite 3690
 sand 3696
 gry to white dolomite 3704
 SLM Corr. 3705
 Total Depth
 PB 3676

ACID TREATMENT No. 2 - Between