


Company - EL DORADO REFG.CO.
 Farm - Benson No. 1.

SEC. 21 T. 12 R. 22 W
 NWc SW

Total Depth. 4161'
 Comm. 10-1-44 Comp. 10-24-44
 Shot or Treated.
 Contractor. B&R Drlg.Co.
 Issued. 11-11-44

County. Trego
 KANSAS



CASING:
 13 3/8" 288' Cem.

Elevation. _____

Production. Dry

Figures Indicate Bottom of Formations.

surface clay	25
lime	40
shale	50
sand	60
shale	70
sand	80
shale & shells	300
shale blue	355
lime & shale brks	405
shale blue	580
shale	640
shale sdy gry	715
sand	970
shale & shells	1030
sand	1060
shale & shells	1080
sand	1130
shale & shells	1345
sand	1523
shale	1545
sand	1560
shale & sand	1685
red bed, shale & shells	1800
anhydrite	1855
red rock	1928
red rock & shale	2040
shells & shale	2420
lime & shale	2480
shale lime & pyrite	2539 ✓
lime & shale	2737
lime cherty	2755
lime & shale	2806
shale & shells	2897
lime & shale	2920
lime	2965
lime & shale	3716
lime	3761
lime brkn	3801
lime cherty & shale	3817
lime	3856
lime & shale	3892
lime	3972
lime & congl	4008
cherty congl	4024
chert	4031
cherty congl	4043
chert & shale	4057
shale red & green	4083
shale sdy	4088
cherty congl	4100
chert & shale	4108
Arbuckle	4125
lime	4161
Total Depth	

Tops:	
Anhydrite	1448
Topeka	3092
Heebner	3308
Toronto	3343
Lansing	3648
Congl	4082
Arbuckle	4110