



SIDE TWO

WELL LOG

23-12-22w

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
Anhydrite	1796	1840		
Topeka	3407			
Heebner	3625			
Lansing	3655			
Arbuckle	4064			

State Geological Survey
WICHITA BRANCH

Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Socks	Type and percent additives
Surface	12 1/4	8 5/8	24#	290'	Common	175	2% gel 3% CaCl
Prod.	7 7/8	5 1/2	14#	4068'	60/40 Poz	200	3% gel, 2% CaCl 10% salt

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Socks cement	Shots per ft.	Size & type	Depth interval

TUBING RECORD

Size	Setting depth	Pecker set at

ACID, FRACTURE, SHOT, CEMENT SOLIFFEZE RECORD

