XV


# WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- HARMS-BURT DRLG. CO.
Farm- Spitsnaugle No. 1

SEC. 15 T. 12 R. 23W
SW SW SE

Total Depth. 3970'
Comm. 8-20-56 Comp. 8-29-56
Shot or Treated.
Contractor.
Issued. 3-23-57

County Trego
KANSAS



Elevation. 2421' RB

Production. Dry

CASING:
8 5/8" 192' w/175 sx cem.

Figures Indicate Bottom of Formations.

| | |
|---|---|
| sdy clay | 30 |
| sand | 150 |
| shale-shells | 845 |
| sand | 970 |
| shale-sand | 1615 |
| shale-red bed | 1760 |
| sand | 1773 |
| sand-shale | 1880 |
| Anhydrite | 1915 |
| shale-shells | 2400 |
| lime-shale | 3260 |
| lime | 3431 |
| lime-shale | 3523 |
| lime | 3970 |
| Total Depth | |

TOPS:

| | |
|---|---|
| Anhydrite | 1880 |
| Heebner | 3680 |
| Toronto | 3700 |
| Lansing Kansas City | 3716 |
| B/Kansas City | 3962 |

DST #1 3795-3807' Open 1 hr.
SI 30 min. Rec. 1140' wtr.
IFP-40# FFP-705# BHP 1085#.

DST #2 3807-3830' Open 1 hr.
SI 20 min. Rec. 435' wtr.
IFP015# FFP-215# BHP-990#.

Ran electric log.