

Flashed

Boorman

THE TEXAS CO.
J. Deines No. 1.


SEC. 19 T. 13 R. 14W
SWc NE
330' fr S & WL in NE $\frac{1}{4}$

Total Depth. 3261'
Comm. 8-20-37 Comp. 10-7-37
Shot or Treated. 3000 Gals.
Contractor. Thayer Drilg.Co.
Issued. 11-13-37

County. Russell

Cable O-3261

NOV 13 1937



Elevation.

CASING:

15 $\frac{1}{2}$ "	345'	7"	2979'
13 "	567'	53/16"	3251'
10 "	865'		
8 $\frac{1}{4}$ "	2455'		

Production. Pot. 1276 B.
No wtr.

Figures Indicate Bottom of Formations.

surface (cellar)	6	shale	2330
clay	10	lime	2335
shale	30	limo & shale	2455
sdv shale	75	brkn lime	2460
shale	165	lime	2475
sand 4BW 165-180	180	shale & shells	2500
shale	210	lime	2540
red rock	230	shale & shells	2550
shale	285	lime	2575
sand	344	shale & shells	2625
iron	383	shale	2640
shale	420	lime	2680
sdv shale	430	shale	2685
sand	460	lime	2840
shale	475	brkn lime	2855
sand	500	lime	2943
red rock	545	shale	2954
sand	550	lime	2968
red rock	555	red rock	2975
sand 2BW 680-700 &	560	lime (Oswald lime	2977
red rock 730'	855	shale 2977)	2984
lime	900	lime	2995
red rock	1030	shale	2999
shale & shells	1085	lime	3065
red rock	1125	sdv lime	3095
shale	1175	lime	3150
brkn lime	1255	shale & red rock	3155
salt	1490	lime	3160
lime & shale	1575	shale & shells	3165
lime	1605	lime	3175
shale	1610	shale & shells	3180
red rock	1635	shale	3192
lime	1665	lime	3195
shale	1675	lime & shells	3205
lime	1690	lime	3210
shale	1700	shale & shells	3220
lime	1720	lime	3230
brkn lime	1740	shale	3235
red rock	1755	lime (Top Siliceous	3245
lime	1790	shale lime 3250#6")	3247
brkn lime	1800	lime	3261
lime	1880	Total Depth.	
red rock	1895		
lime	1950		
shale	1955		
brkn lime	1980		
lime	2000		
brkn lime	2030		
lime	2065		
brkn lime	2075		
red rock	2095		
lime	2125		
shale	2130		
lime	2150		
shale	2155		
lime	2200		
shale	2205		
lime	2275		
brkn lime	2295		
limo	2300		