HOWARD BRUNSON
Gaynor No. 1.

SEC. 19 T. 13 R. 14W
SEc NW

Total Depth. 3197'
Comm. 12-2-37 Comp. 1-4-38
Shot or Treated. 500 Gals.
Contractor. Howard Brunson
Issued. 4-2-38

County. Russell

APR 2 1938

CASING:
15 1/2" 285'
13 3/8" 510'
10" 800'
8" 2395'
6" 2925'
5" 3184'



Elevation.

Production. Pot. 1578 B.

Figures Indicate Bottom of Formations.

clay & shells	20	lime	2245
shale blue	95	shale blue	2255
sand	105	lime	2260
shale lgt	125	shale blue	2270
shale red	135	lime	2300
shale blue	200	shale blue	2310
shale red	210	lime	2320
shale blue	235	shale blue	2325
sand	285	lime	2330
iron & sand	320	shale	2350
shale blue	365	lime	2352
sand	400	shale drk	2390
shale blue	425	lime	2410
sand	435	shale lgt	2440
shale red	475	lime	2455
sand	483	shale & shells	2560
shale red	487	shale	2585
sand	490	lime	2605
shale red	795	shale	2610
lime anhydrite	830	lime	2635
shale red	960	shale	2645
shale blue	1015	lime	2730
shale red	1065	shale	2733
shale blue	1180	lime	2870
salt	1420	shale	2880
shale blue	1430	lime	2883
lime	1495	shale	2890
lime & shale	1520	lime	2908
lime	1535	shale red	2914
shale blue	1540	lime	2935
shale red	1550	SLM Corr. 2922	
shale blue	1595	lime	2933
lime	1660	shale	2940
red rock	1675	lime	3055
lime	1705	shale	3060
shale blue	1715	lime	3120
lime	1795	shale	3125
shale red	1810	lime brkn	3140
lime brkn	1830	lime	3150
shale blue	1835	lime brkn	3165
lime	1870	conglomerate	3169
shale blue	1875	shale	3176
shale red	1880	lime	3180
lime	1900	shale green	3183
shale blue	1910	dolomite	3197
lime	1920	Total Depth.	
shale red	1930		
lime	1980	good sh free oil 2912-22	
shale blue	1985	Hole filled 2500' with oil when	
red rock	2000	plug was drilled at 3197	
lime	2050	Temp. Pot. 1578 B.	
shale red	2065		
lime	2190		
shale blue	2195		
lime	2230		
shale	2235		