WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas

CITIES SERVICE OIL CO.
Johnson "C" No. 1.

SEC.22 T.13 R. 15 W
NWc NE
330'S 330'E of N¼ Cor.

Total Depth. 3369'
Comm. 10-18-42 Comp. 11-3-42
Shot or Treated. None
Contractor. Earl F.Wakefield
Issued. 1-16-43

County. Russell



CASING:
8 5/8" 353' Cem.
4 1/2" 3180' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

surface clay	0-80
iron	95
shale & shells	115
sand	125
shale & shells	283
red rock	353
sand hd	358
shale & shells	370
sand	385
iron & sand	423
sand hd	429
sand & iron	495
shale & shells	620
red bed	810
shale	840
red bed	915
shale & red bed	958
anhydrite	990
red rock, shale, shells	1155
shale & lime shells	1341
shale & shells	1445
salt & shale	1570
lime brkn	1957
lime cherty	1965
lime sdy	1972
lime brkn	2030
shale & shells	2134
lime brkn	2476
shale	2530
lime	2572
shale & lime	2639
lime	2665
shale & shells	2751
lime	2761
lime brkn	2790
lime	2888
lime w/shale strks	2911
lime	3043
shale	3076
lime	3200
shale	3210
lime	3243
lime brkn	3264
shale	3279
shale & lime	3332
cherty conglomerate	3350
lime	3369
Total Depth.	

11-23-42 perf. by Lane-Wells as follows:
10 shots 3100-09,
1 bbl. wtr./hr
12 shots 3089-93, no inc.
12 shots 3105-09, bailing
8 bailers wtr per hr 75' off btm, no oil

Tops:

Lansing	3065
Arbuckle	3349
Penetration	20