WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY,
Union National Bank Bldg, Wichita, Kansas.

35-13-15W

Plotted Texas Co.

THE HARTMAN AND BLAIR OIL CO.
Baier No. 1.

SEC. 35 T. 13 R. 15W.
SEc SW SE


Total Depth. 3315
Comm. 5-29-35 Comp. 7-4-35.
Shot or Treated.
Contractor. Braden-McClure Drlg Co.
Issued. 8-10-35.

AUG 10 1935

County. Russell. **Plotted**

CASING.

15½" 357' 8¼" 2530'
13 3/8" 546' 6 5/8" 3049' UR 3228'
10" 940'



Elevation.

Production. Pot. 426 B.

Figures Indicate Bottom of Figures.

| | |
|---|---|
| clay | 15 |
| slate | 65 |
| shale dark | 105 |
| shale grey | 160 |
| shale blue | 225 |
| shale light | 240 |
| HFW | |
| lime | 250 |
| shale white | 265 |
| red rock | 275 |
| shale light | 290 |
| red rock | 310 |
| slate grey | 335 |
| shale | 365 |
| lime sdy | 385 |
| shale dark | 415 |
| shale | 445 |
| mud blue | 460 |
| shale blue | 490 |
| slate blue | 515 |
| shale and sand | 538 |
| red rock | 543 |
| sand red | 580 |
| red rock | 928 |
| anhydrite lime | 940 |
| corrected Meas. | 940=930 |
| anhydrite | 965 |
| bailing hole. | |
| red rock | 1122 |
| shale blue | 1125 |
| lime and shells | 1165 |
| red rock | 1215 |
| shale and shells | 1225 |
| red rock | 1230 |
| shale and shells | 1240 |
| shale blue | 1310 |
| broken lime | 1330 |
| salt | 1370 |
| rock salt | 1440 |
| salt | 1565 |
| shale shells | 1585 |
| lime & shale | 1630 |
| lime | 1649 |
| shale blue | 1658 |
| broken lime | 1675 |
| lime | 1715 |
| shale brown | 1730 |
| lime | 1750 |
| shale | 1760 |
| lime | 1813 |
| shale and shells | 1824 |
| red rock | 1828 |
| shale blue | 1835 |
| lime | 1855 |
| lime white | 1872 |
| shale light | 1880 |
| lime grey | 1960 |
| shale | 1975 |
| lime | 2010 |
| lime white | 2025 |
| lime grey | 2040 |
| shale blue | 2046 |
| lime | 2071 |
| shale | 2075 |
| lime | 2100 |
| shale | 2105 |
| lime | 2172 |
| red rock | 2180 |
| 1 BW HH 2150-2165 | |
| lime white | 2215 |
| shale blue | 2221 |
| lime | 2245 |
| red rock | 2250 |
| lime | 2275 |
| shale blue | 2285 |
| lime | 2315 |
| shale blue | 2325 |
| lime | 2330 |
| shale | 2350 |
| lime | 2370 |
| shale | 2375 |
| lime | 2382 |
| shale & shells | 2415 |
| shale | 2417 |
| lime | 2425 |
| shale | 2463 |
| lime | 2470 |
| shale | 2495 |
| lime | 2498 |
| shale | 2530 |
| lime | 2555 |
| shale | 2570 |
| shale blue | 2580 |
| lime and shale | 2620 |
| lime grey | 2640 |
| shale blue | 2652 |
| lime grey | 2657 |
| shale & shells | 2670 |
| shale | 2690 |
| lime | 2700 |
| shale | 2728 |
| lime | 2774 |
| shale blue | 2785 |
| show oil 2780-2790 | |
| lime | 2910 |
| lime white | 2945 |
| lime grey | 2990 |
| lime | 3024 |
| shale | 3030 |
| correction 3030=22 | |
| shale | 3027 |
| lime white | 3040 |
| shale | 3045 |
| red rock | 3049 |
| shale | 3064 |
| lime | 3080 |
| shale blue | 3084 |
| lime grey | 3110 |
| ½ BW 3090-3100 | |
| 1 BW 3100-3110 | |
| lime grey | 3120 |
| lime | 3132 |
| shale | 3135 |
| 4 BW 3155-60 | |
| lime | 3170 |
| lime grey | 3180 |
| lime | 3220 |
| 4 BWPHR 3220 | |
| lime | 3228 |
| bailed 1½ BW | |
| lime | 3231 |
| red rock | 3235 |
| shale | 3238 |
| show oil 3247 | |
| lime | 3247 |
| lime white | 3250 |
| shale and lime | 3255 |
| lime | 3258 |
| shale dark | 3266 |
| lime white | 3280 |
| lime grey | 3286 |
| shale blue | 3292 |
| lime grey | 3300 |
| shale green | 3310 |
| lime | 3315 |
| Total Depth. | |

3310 to 3315 filled
1800' with oil in 40 Min