

WOLF CREEK OIL COMPANY
 Dillner No. 1.


SEC #6 T. 13 R. 15W
 SW c SW 1/4

Total Depth, 3329'
 Comm. 3-7-36 Comp. 4-30-36
 Shot or Treated,
 Contractor.
 Issued, 5-9-36

County, Russell

MAY 9 1936

CASING.
 15 " 347'
 12 " 623'
 10 " 929'
 8 1/4" 2550'
 6 5/8" 3050' UR 3197' 6"
 5 3/16" 3290'



Elevation.

Production, Dry

Figures Indicate Bottom of Formations.

shale	35	lime	2337	Light show of oil & gas 2805
clay yellow	50	shale	2345	Good show of oil 3138-3142
shale dark	80	lime	2383	Oil from 3316-3319
shale HFW	245	shale	2405	filled up 125' 30 min.
sandy shale HFW	255	lime	2450	Topped Siliceous lime
red rock	305	shale	2460	April 20th, hole started
shale	315	lime	2465	filling up with oil from
red rock	325	shale	2480	3316-3319
shale grey	330	lime	2505	
shale	415	shale	2525	Total Depth 3320-
sand wtr HFW	425	lime	2545	Production 50 Bbl per day
shale blue	515	shale & shells	2585	natural-getting ready to
shale grey	520	shale blue	2610	acidize. Deepened 9'
shale	530	lime	2680	and abandoned.
red rock	565	shale	2690	
shale blue	580	lime	2695	
red rock 11EW	910	shale	2730	
lime	965	shale & shells	2745	
red rock	1110	lime	2775	
shale grey	1120	correction in measurement		
shale	1140	of 15 ft. 2730-2715		
red rock	1200	shale 1EWPH	2780	
shale grey	1270	lime	3015	
salt	1585	shale	3025	
lime	1625	lime Dodge	3040	
shale	1640	red rock	3047	
lime	1655	lime	3053	
shale	1665	shale	3063	
lime	1675	K.C. lime	3074	
shale	1685	shale	3075	
lime	1700	lime	3084	
red rock	1725	shale	3089	
lime	1750	lime	3132	
shale	1760	shale	3137	
lime	1810	lime	3147	
shale	1815	shale	3150	
red rock	1835	lime	3235	
lime	1860	shale	3240	
shale	1895	2 BW 3245		
lime	1960	lime	3260	
shale	1985	shale	3273	
lime	2000	lime	3290	
shale	2015	shale & lime	3300	
lime	2035	shale	3305	
shale	2055	shale green	3310	
red rock	2060	lime	3329	
lime	2095	Total Depth		
shale blue	2105			
lime	2160			
shale	2180			
red rock	2185			
lime	2230			
shale	2245			
lime	2320			
shale	2330			