

THE TEXAS CO.
A.D.Jellison No. 1.


SEC.13
NEc SE

T.13

R.15 W

Total Depth. 3253'
Comm. 5-14-43 Comp. 6-2-43
Shot or Treated.
Contractor. Kiowa Drlg.Co.
Issued. 6-26-43 Rotary O-3253

County. Russell



CASING:
8 5/8" 855' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

shale, iron, steel, sd	185 ✓
sand & iron	385 ✓
shale & red rock	575
red rock	665
sand & red rock	805
red rock	852
anhydrite	970
red rock & shale	1015
shale & shells	1100
sand	1135
shale & shells	1250
salt & shale	1420
lime & shale	1785
lime	1965
lime & shale	2195
shale & shells	2695
lime	3010
lime	3235
Arbuckle	3253
Total Depth.	

Tops:
Topeka 2710
Lansing 2966
Eros Arbuckle 3233
Solid Arbuckle 3244

Cores:
3010-14 4' rec.
 1' show oil
 3' hd tight lime
3235-39 3 1/2' rec.
 1 1/2' sft lime
 3 1/2' hd lime, chert,
 & shale
3239-53 2' rec.

Run Schlumber Test
Dry & Abnd.