

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas

CITIES SERVICE OIL CO.
Marsh "B" No. 2.

SEC. 30 T. 14 R. 12 W
CSL SE SE
330' N 660' W SE Cor.

County. Russell

Total Depth. 3108'
Comm. 5-22-43 Comp. 6-18-43
Shot or Treated. None
Contractor. Corbett-Barbour Drlg. Co.
Issued. 8-14-43



CASING:
8 5/8" 318' Cem.
5 1/2" 3104' Cem.

Elevation.

Production. Deptho. Pot.
1046 BO, No wtr
Figures Indicate Bottom of Formations.

sand	0-75
red bed	600
anhydrite	630
shale & shells	1240
shale & lime	1415
lime & shale	1540
lime	1650
lime & sand	1750
lime & shale	1830
shale & lime	2295
lime	2350
shale & lime	2515
lime	2555
lime & shale	2595
lime	2755
shale & lime	2800
2800 equals 2788 SIM	
shale & lime	2815
lime	3015
lime & shale	3070
lime	3105
3105 Rot. TD equals 3105 SIM	
sand	3108
Total Depth.	

Top Gorham Sand 3104
Penetration 4

Fillup: 1080' oil in 45 min.
1400' oil in 1 hr, 10 min.
1700' oil in 1 1/2 hrs
2500' oil in 3 3/4 hrs