

FINSTON-DAVIS-GORE
 Michel No. 2.

SEC.36 T.14 R. 14W
 CEL SE NW

Total Depth. 3163'
 Comm. 9-29-40 Comp. 11-15-40
 Shot or Treated.
 Contractor. Harry Gore
 Issued. 12-14-40

County. Russell



CASING:
 15 1/2" 38'9"
 10 " 720' UR 737'
 8 1/4" 2170' UR 2440'
 6 5/8" 2920'
 5 3/16" 3140' UR 3156'

Elevation.

Production. Pot. 3014 B.

Figures Indicate Bottom of Formations.

cellar	10	shale blue	2215
sand dry	35	lime	2220
slate	90	shale blue	2225
shale sdy	105	lime	2240
sand wtr	110	slate & shells	2320
red rock	125	lime	2350
slate gy	145	shale blue	2375
sand	155	lime	2420
red rock	175	slate blue	2435
shale blue	200	lime	2442
sand wtr	242	shale sdy	2455
iron	250	lime	2463
shale blue	290	shale blue	2490
shale sdy	310	lime shell	2493
slate	365	shale blue	2522
red rock	700	shale & shells	2585
lime anhydrite	737	shale blue	2590
corrected meas.	755-765	lime Topeka	2843
red rock	765-915	shale blue	2853
shale blue	950	lime Dodge	2869
red rock	1010	shale blue	2873
slate blue	1090	red rock	2879
salt	1395	shale blue	2900
lime	1405	lime K.C.	2915
red rock	1415	shale lgt	2918
lime	1420	lime - oil	2922
slate & shells	1450	lime - salt	2925
lime	1470	lime hrd	2942
shale blue	1480	lime sft	2947
lime	1495	lime hrd	2972
shale lgt	1505	shale blue	2975
lime	1510	lime	3013
red rock	1513	shale blue	3017
lime	1555	lime	3065
red rock	1565	lime & shale	3080
lime	1595	lime	3090
shale blue	1605	lime brkn	3100
lime	1615	lime	3108
red rock	1625	shale blue	3125
lime	1755	lime	3130
red rock	1770	lime & shale	3140
lime	1780	shale blue	3142
red rock	1800	lime w/shale brks	3152
shale & shells	1845	lime & cong.	3156
lime	1892	lime	3159
red rock	1900	sand - oil	3163
lime	1920	Total Depth.	
shale & shells	1970		
red rock	1985		
lime	2030	sh oil 2270-75	
		sh oil 2595	
		sh oil 2860	
		sh oil & gas 2918-20	
shale & shells	2165		
shale sdy	2170	4 BW 90-105	
lime	2172	HPW 145	
shale blue	2175	2 BW 570-80	
red rock	2185	HPW 2165-70	
lime	2190		