

24-14-15W

Total Depth. 3253
Comm. 12-27-34 Comp. 3-10-35.
Shot or treated.
Contractor. Broadwater Drilling Co.
Issued. 3-30-35.

County, Russell.

MAR 30 1935



CASING.

20"	81'	8"	2465'
15 ¹ / ₂ "	377'	6"	3078'
10"	872'	53/16"	3246'

Elevation.

Production, Pot. 804 B.

Figures Indicate Bottom of Formations.

clay yellow	65	shale	2075	shale red	3015
sand	80	lime	2100	shale	3020
shale	155	shale red	2125	lime	3085
sand	165	lime	2170	2 BW 2855	
4 BW 155-165		shale	2185	1 BW 2905-2915	
shale	195	lime	2215	3 BW 3055	
shale red	205	shale	2220	shale	3090
10 BW 205-215		lime	2240	lime	3120
sdly lime	215	shale	2255	shale	3125
shale red	230	lime	2270	lime	3148
shale	270	shale	2275	shale	3152
shale red	300	broken lime	2285	show gas 3164-3168	
sand	305	no log	2290	lime	3190
shale	355	broken lime	2315	shale	3200
sdly lime	365	lime	2325	lime	3225
shale	410	shale and shells	2350	shale	3233
lime	420	shale	2360	lime	3247
water 416-420 HFW	450	lime	2365	??	3250
sand	475	shale	2400	shale	3263
shale	480	lime	2410	lime	3264
sand	490	shale red	2425	3264 equals 3253	
shale	495	shale	2432	Total Depth.	
shale red	510	lime	2443		
lime	530	shale	2450		
shale red	870	lime	2456		
lime	915	2456 equals 2465 COM.			
shale red	1070	shale	2475		
shale blue	1110	lime	2500		
shale red	1185	shale	2510		
shale	1260	shale and shells	2525		
lime	1270	shale	2530		
shale	1275	lime	2545		
shale red	1280	shale	2550		
salt	1525	lime	2575		
shale	1540	no log	2580		
lime	1558	lime	2595		
broken lime	1580	shale	2600		
shale	1590	lime	2615		
lime	1640	shale	2675		
shale red	1660	lime	2680		
lime	1695	broken lime	2710		
shale	1715	lime	2725		
lime	1755	shale	2735		
shale red	1770	lime	2760		
broken lime	1808	shale	2765		
shale	1815	lime	2825		
lime	1904	shells	2829		
shale red	1915	lime	2920		
lime	1940	shale	2925		
shale	1950	lime	2965		
lime	1970	shale	2969		
shale	1985	broken lime	2975		
lime	2030	shale	2985		
broken lime	2065	lime	3005		