


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
Wichita, Kansas

Company - JOHN LINDAS OIL, INC.
Farm - Ehrlich No. 2 A

SEC. 1 T. 14 R15W
SE SW NW

Total Depth. 2945
Comm. 2-7-50 Comp. 3-10-50
Shot or Treated.
Contractor. H & M Drlg. Co.
Issued. 4-8-50

County. Russell
KANSAS



CASING: 13 3/8" 420'
10" 585'
8" 931'
6" 2494'
5" 2887'

Elevation. _____

Production. Dry

Figures Indicate Bottom of Formations.
Casing all pulled.

Post rock	35	Lime	2315
Shale	150	Shale	2325
Shale & shells	160	Shale & shells	2370
Shale	220	Shale	2380
Sand	240	Lime	2410
Shale	310	Shale	2425
Red rock	320	Shale & shells	2490
Shale	370	Iron	2494
Sand	385	Shale	2507
Shale	420	Sand	2511
Sand	430	Sandy shale	2527
Shale	480	Sand	2536
Sand	495	Shale	2579
Shale	500	Shale & lime	2595
Sand	510	Shale	2599
Shale	515	Lime	2625
Sand	560	Shale & shells	2630
Iron-hard	565	Shale	2645
Sand & iron	570	Shale & shells	2686
Red rock	575	Sandy shale	2693
Sand & iron	585	Shale & shells	2725
Red rock	595	Lime	2765
Sand	605	Shale	2778
Red rock	914	Lime	2847
Lime	915	Sandy	2860
Anhydrite lime	970	Lime	2912
Red rock	1115	Shale	2915
Shale	1150	Lime	2924
Red rock	1210	Shale	2927
Shale	1310	Lime	2945
Salt	1585	Total Depth	
Lime	1715	Tops-Scout:	
Red rock	1740	Topeka	2780
Lime	1755	Water record:	
Shale	1765	1 B" 35-50,	
Red rock	1770	15 BW 240'	
Lime	1815	HF# 420'	
Red rock	1840	Trace oil & gas @ 2686'	
Lime	1875	Oil show 2781-84'	
Shale	1880	1/2 BW 2815-2820'	
Lime	1960	7 BW 2932-45'.	
Red rock	1970		
Lime	2025		
Shale	2045		
Lime	2085		
Red rock	2095		
Lime	2155		
Red rock	2170		
Lime	2200		
Shale	2205		
Lime	2215		
Shale	2225		
Red rock	2235		
Lime	2260		
Shale	2270		