

STANOLIND OIL & GAS CO.  
C.A. Mermis No. 6


SEC. 5 T. 14 R. 15W  
SEC NE  
330' N SL 2310' E WL

County. Russell

Total Depth. 3078'  
Comm. 6-7-36 Comp. 7-27-36  
Shot or Treated.  
Contractor.

Issued. 9-12-36

Cable O-3078'



CASING:

16 "	22'	
13 "	414'	Pulled
10 3/4 "	918' 2"	Pulled
8 5/8 "	2513'	Pulled
7 "	3040'	

Elevation.

Production. Pump 548 B.  
No water.

Figures Indicate Bottom of Formations.

soil	11	shale & shells	2145
clay yellow	15	lime	2150
quick sand	28	shale	2185
shale blue	80	lime	2205
lime hrd	90	shale & shells HFW	2215
shale blue	185	showing of gas	2210-15
shale light	220	shale	2230
shale gritty	265	lime	2235
shale light	300	red rock	2245
water sand	305	shale	2440
sdv shale	315	lime	2445
shale dark	335	shale	2510
water sand	358	lime	2520
mud blue	380	shale	2560
lime hrd	390	lime	2570
shale blue HFW	505	shale	2595
red rock	545	lime	2615
shale red	550	shale	2635
mud blue	575	lime	2660
shale blue	605	shale	2750
sand red	620	lime	2780
red rock	675	show of oil	2753-60
shale blue	690	lime	2795
sand red	695	shale	2805
red rock	780	sdv lime	2825
shale red	890	lime	2995
red rock	924	shale	3008
lime anhydrite	940	lime	3015
limo white	965	shale & shells	3028
shale red	985	red rock	3034
red rock	1075	shale	3041
shale red	1140	lime (sh oil-Top Oswald)	3044
red rock	1235	lime	3060
salt	1580	shale	3065
shale blue	1590	lime	3078
lime	1595	No sh of water	
shale blue	1650	Total Depth	
shell & shale	1700		
red rock	1710		
lime	1745	Potential Test Completed	8-11-36
shale	1750		
lime	1795		
shale	1825	Oswald Lime from	3041-3078
lime	1830		
shale	1845		
lime	1860		
shale	1915		
lime	1945		
red rock	1960		
lime	1990		
shale	2045		
lime	2055		
shale	2080		
red rock	2090		
limo	2095		