


STANOLIND OIL & GAS CO.
C.A. Morris No. 13 11

SEC. 5 T. 14 R. 15W.
SE NENE
1710' N of S.L. 2310' E of WL

Total Depth. 3106
Comm. 9-19-37 Comp. 10-27-37
Shot or Treated.
Contractor.
Issued. 12-11-37

County Russell.



CASING. Cable

16" 42'
7" 3053'

Elevation.

Production. Pot. 206 B.

Figures Indicate Bottom of Formations.

collar soil	3'	lime	2245
shale	115	red rock	2250
shale blue	195	lime	2280
sand	210	shale	2 285
shale	225	lime & shale breaks	2325
shale grey	240	limo shells and shale brks	2365
shale red	265	lime and shale	2415
shale grey	275	lime and shale brks	2430
shale red	290	shale brown	2445
shale	295	limo and shale breaks	2475
sand HFW	335	shy shale	2500
shale	365	shale blue	2520
red rock	375	lime	2535
shale red	385	shale	2580
shale blue	400	lime	2590
shale	430	lime and shale	2610
shale red	445	shale and shells	2640
shale blue	455	lime	2670
red rock	500	shale	2710
sand	545	lime and shale breaks	2730
red rock	550	shale	2737
water sand	570	lime	2756
shale red	595	shale	2769
red rock	690	limo Topoka	2769 2995
shale red	730	small show oil	2772
red rock	815	shale	3008
shale red	855	Dodge limo	3022
red rock	925	shale limo red rock and	
shale red	936	shale	3035
Anhydrite lime	982	red green and wh shale	3050
red rock	1055	S.L. Corr.	3050 equals 3048
shale red	1130	lime Top Oswald	3048 3086
shale blue	1165	Pay 3078-3081	
red rock	1255	Broken lime	3100
shale blue	1275	lime	3106
salt	1580	best pay 3103-3106	
shale blue	1600	Total Depth.	
lime	1650		
lime shale breaks	1705	Oswald limo 3047-3106	
lime	1710		
red rock	1730	1st 4 hr test pumped 34 Oil 9 BW	
lime	1775	2nd 4 hr test pumped 34 oil 13 BW	
blue rock	1785		
lime	1970		
shale and lime	1990		
lime	2045		
shale blue	2050		
shale red	2060		
lime	2090		
shale red	2100		
lime	2170		
red rock	2185		
lime	2210		
shale blue	2215		